

# PANCLIPSS MTW 304 STAINLESS



## Features:

- #10-9 full stainless steel fastener has square #2 drive
- Thread designed to improve holding strength into plywood and MDF substrates vs our #10-12 fasteners.
- 304 Stainless Steel parts carry a current Miami-Dade County Product Listing # L15-0602.01
- Applications include panel clip attachment to wood substrate, window installations into wood substrate.

MIAMI-DADE COUNTY  
LISTED

## Specifications

Torsional: 60 in-lbs  
Pull out 3/4" PLY 520 lbs ult  
Pull out 5/8" PLY 401 lbs ult  
Pull out 1/2" PLY 361 lbs ult  
Pull out 7/16" OSB 192 lbs ult  
304 Stainless Steel or 316 Stainless Steel

Ultimate values listed are the result of laboratory testing. Wood substrate strengths and availabilities vary by region and supplier. Specific job conditions should be considered and appropriate safety factors applied when specifying the proper fasteners.

ANSI/ASME B 18.6.1 COO: Taiwan

## Selection

<u>304 Stainless Steel</u>	<u>Qty/Box</u>	<u>Part#</u>
#10 x 1" SQ2 TP17	5,000	DMIP31010D
#10 x 1-1/2" SQ2 T17	2,500	DMIP31015D
#10 x 2" SQ2 TP17	2,000	DMIP31020D

Miami-Dade County Listed Product - Certification L 15-0602.01

<u>316 Stainless Steel</u>	<u>Qty/Box</u>	<u>Part#</u>
#10 x 1-1/2" SQ2 T17	2,500	DMIP3161015D

## Installation

#2 square drive required.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Suggested drill speed is 1800 rpm.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Suggested 1" minimum penetration into substrate.

**Limitations:** Not recommend for installation by impact drivers. Contact DMI for MSDS information