

#9 Trugrip Stone Coat Fastener



#9-15 Trugrip™

Popular installation of stone coated metal roofing panels to wood substrates, Also popular for ridge vent installation to wood substrates. 1/4" HWH and sharp point.

Features:

High hex washer head provides driving stability
Climaseal silver coating for corrosion protection
Sharp point for penetrating sheet metal panels
Anti Pig Tail Technology

Specifications

1/4" HWH , Sharp Point

Torsional: 50 in-lbs

Tensile: 1800 lbs. min.

Shear: 1200 lbs min.

Painted and Packaged in the U.S.A.,
Base part is imported

Selection

Available Sizes

Qty/Box

Part#

Please call for availability

Installation

1/4" Hex drive required, LSC spring clip suggested.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Suggested drill speed is most substrates is 1800 rpm.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Suggested 1" minimum penetration into substrate.

Approximated values are average ultimate values.
Values may change with strength and condition of substrate wood.

Limitations: Not recommended for pressure treated wood substrates. Not recommended for aluminum or copper roofing panels. Not recommend for installation by impact drivers. Contact DMI for MSDS information

To find a distributor of this or other DMI products please visit www.directmetalsinc.com or call 855-800-8878