

## Rivet Type / Grip Range


Size/	Rivet	* Body	Decimal Inches	Approx. Fraction	
Туре	Dia.	Length	Grip Range	Min	Max
31	3/32	3/16	.0206	3/128	1/16
32	3/32	1/4	.0312	3/128	1/8
34	3/32	3/8	.1225	1/8	1/4
41	1/8	3/16	.0306	3/128	1/16
42	1/8	1/4	.0612	1/16	1/8
43	1/8	5/16	.1218	1/8	3/16
44	1/8	3/8	.1825	3/16	1/4
45	1/8	7/16	.2531	1/4	5/16
46	1/8	1/2	.3137	5/16	3/8
48	1/8	5/8	.3750	3/8	1/2
410	1/8	3/4	.5062	1/2	5/8
52	5/32	1/4	.0612	1/16	1/8
53	5/32	5/16	.1218	1/8	3/16
54	5/32	3/8	.1825	3/16	1/4
56	5/32	1/2	.2537	1/4	3/8
58	5/32	5/8	.3750	3/8	1/2
510	5/32	3/4	.5062	1/2	5/8
512	5/32	1-1/16	.6275	5/8	3/4
516	5/32	1-3/16	.87 - 1.0	7/8	1
62	3/16	1/4	.0612	1/16	1/8
63	3/16	5/16	.1218	1/8	3/16
64	3/16	3/8	.1825	3/16	1/4
66	3/16	1/2	.2537	1/4	3/8
68	3/16	5/8	.3750	3/8	1/2
610	3/16	13/16	.5062	1/2	5/8
612	3/16	15/16	.6275	5/8	3/4
614	3/16	1-1/16	.7587	3/4	7/8
616	3/16	1-3/16	.75 - 1.0	3/4	1
618	3/16	1-1/2	1.0 - 1.1	1	1-1/8
620	3/16		1.1 - 1.2	1-1/8	1-1/4
622	3/16		1.2 - 1.3	1-1/4	1-3/8
84	1/4	1/2	.1225	1/8	1/4
86	1/4	5/8	.2537	1/4	3/8
88	1/4	3/4	.3750	3/8	1/2
810	1/4	7/8	.5062	1/2	5/8
812	1/4	1"	.6275	5/8	3/4
814	1/4	1-1/8	.7587	3/4	7/8
816	1/4	1-1/4	.75 - 1.0	3/4	1



## Mill finish stainless steel rivets

Available Sizes	Qty/Box	Part#
#43 1/8" .126" to	.187" 5000	DMI2L1290
#44 1/8" .188" to	.250" 5000	DMI2L1300
#46 1/8" .31" to .3	37" 5000	DMI2L460S

Painted Rivets available in 15 std colors.Available SizesQty/BoxPart##43 1/8" .126" to .187" 5000DMI2L1290(001)#44 White and Bronze 5000DMI4SSR44PW#46 in Black, Brown, Light Gray only <SE Whse</td>



\* Body Length is approximate (& doesn't include countersunk or large flange.)

## **About Pop Rivets**

Fasten joints without access to reverse side. Insert rivets - the retracting jaws in the setting tool pull the mandrel head into the rivet body on the reverse side until the mandrel breaks. The high clinch action pulls the parts together for a tight, vibration-proof fastening.