WoodZIP SS 304 Stainless

WOODZIP™ SS Full Stainless Steel Fasteners

The WoodZip SS fasteners offer the same performance you have come to expect from the DMI WoodZip line of fasteners combined with the corrosion resistant properties of full 304 Stainless Steel fastener. Designed for metal, PVC and Polycarbonate panel installation to wood substrates. Assembled with high quality bonded washers. Please note predrill of panel is required for installation. Packaged 250 pieces per bag.

Features:

Full 304 Stainless Steel 18-8 stainless steel
Full passivation for added corrosion resistance
Large diameter washer available
#14 diameter WoodZIP SS for translucent panel installations





Specifications

#9-15 Full 304 Stainless Steel
Passivated, bonded 14mm
EPDM/304 SS washer 1/4" HWH
Head sharp point with single lead
thread.

#10-15 Full 304 Stainless Steel Passivated, bonded 14mm, 16mm or 3/4" EPDM/304 SS washer 1/4" HWH Head TP-17 cut point with HILO dual stage lead thread

#14-10 Full 304 Stainless Steel Passivated, bonded 3/4" Neo/304 SS washer 3/8" Hex Head A point with type A thread.

Manufactured in Taiwan.

Selection

<u>Sizes</u>	Washer Qty/Box		Part#
#9-15 x 1-1/2"	14mm	2,500	DMI4H9SS150
#10-15x1-1/2"	16mm	2,500	DMI4HSS150
#10-15x1-1/2"	3/4"	2,500	DMI4HSS15034
#10-15x2"	3/4"	2,000	DMI4HSS20034
#14 x 1-1/2"	3/4"	2,000	DMI4H14SS15034
#14 x 2-1/2"	3/4"	2,000	DMI4H14SS25034

Installation

LSC spring clip suggested.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Suggested drill speed is most substrates is 1800 rpm.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Suggested 1" minimum penetration into substrate.

Limitations: Not recommend for installation by impact drivers.

Contact DMI for MSDS information