

Direct*Seal Universal Closure Roll



Direct*Seal universal long life closure rolls are designed to seal gaps between trims/flashings and metal roofing panel profiles. Other popular applications include window and door installation, metal building base plate and sill sealing. When compressed Direct*Seal will become a water, pest, wind and dust barrier.

**Easy peel adhesive strip and starter strip
Long life UV Protection
No asphalt content
No staining or scratching of panel finish**



Specifications

Foam with UV resistant coatings.

No asphalt content

Minimum of 25% compression is required for performance as dust, sound protection, pest resistance and thermal insulation.

50% Compression required for wind, air and rain protection up to 20 psf.

Country of Origin :

United States of America

DMI does not test applications or field conditions for this product as it may vary per application, and must be tested as an assembly.

Please be sure to register warranty after installation.

Selection

<u>Available Sizes</u>	<u>Qty/Box</u>	<u>Part#</u>
1" x 1" x 20'	20	DDS101020
1-1/2" x 1-1/2" x 20'	10	DDS151520
2" x 2" x 10'	10	DDS202010

Installation

Peel back adhesive release paper beyond the length of product you need. Adhere adhesive side to metal flashing/ clean surface.

Immediately dispose of release paper in a safe fashion. Do not leave release paper on roofing surface.

Install the metal flashing per panel manufacturers recommendations.

When allowable per panel manufacturers specifications it is suggested the fasteners be installed through the flashing and through the center of the Direct*Seal product into the substrate.

Safety, Based on current data, this product is not hazardous in the meaning of the Hazardous Material Regulations. Do not eat. We recommend that you take care, in use and disposal of this product. Make sure to dispose of adhesive release paper immediately after peeling, do not leave on roof surface.