



#12-24 PURLIN FASTENERS

Designed for installation of insulation and membrane attachment to medium and heavy steel purlins from 16 ga to 1/4" thick steel. #12 diameter 24 threads per inch, #3 square drive. Shank diameter is smaller than that of the drill point and the outside thread diameter, allowing thick metal to be drilled and cleared of chips before threads tap into metal.



Pull out	Pull out	Thread: .207
18GA:375	3/16":2300	HeadH .110
16GA:599	1/4": 2300	Tensile2300

Available Sizes	Qty/Box	Part#
#12 x 1-3/8" SQ#3	1,000	Discontinued
#12 x 2-3/4" SQ#3	1,000	Discontinued
#12 x 3-3/4" SQ#3	1,000	DMI2C4325995B
#12 x 4-3/4" SQ#3	1,000	DMI2C4335995B
#12 x 5-3/4" SQ#3	1,000	DMI2C4345995B
#12 x 6-3/4" SQ#3	500	DMI2C4355995B
#12 x 7-3/4" SQ#3	500	Discontinued

Also Ideal for metal roofing panel clip installation into steel purlins. Grey Senti-XP coating. 3/4" of the length of the fastener is drill bit and unthreaded lead.

Limitations: Not recommend for installation by impact drivers.

Contact DMI for MSDS information

Sales are done through DMI registered distributor network only please contact 855-800-8878 to find a registered distributor or email distributors@directmetalsinc.com