



Phone: (239) 599-8527 Fax: (239) 599-8545
 Website: www.directmetalsinc.com
 Email: info@directmetalsinc.com

DMI RETROFIT RESIDENTIAL MASTERFLASH

**Electrical Mast Connection
 DMI Retrofit Residential
 MasterFlash PN DMIEMC101BS**

Specifically designed for the Residential roofing Industry.

DMI Retrofit Residential Masterflash are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light.

The base is designed to mold to most configurations and roof pitches regardless of pipe location.

Easy to see pipe diameter markings make for an easy on-site installation.

Built in 20 deg pitch allows adaptability to almost any roof pitch including 45 deg.

No hassle stainless steel gripper to secure retrofit application.

Tested to continuous 212 deg F high temperature resistance.
 Tested to -67 deg F low temperature resistance.
 Advanced ozone resistance tested to 70 hours @ 500 pphm.



Part# DMIEMC101BS

For Electrical Mast 0" - 5-3/8"
 Top Opening closed
 Cut to suit pipe size 0" - 5-3/4"
 Base dimensions 15" x 15"



10 Pieces per carton.



DMI Retrofit Residential Masterflash is available for purchase through registered Direct Metals, Inc. distributors.