



RUBEX

RUBEX NON-SKINNING BUTYL SEALANT

RUBEX NON-SKINNING

Product Overview: Rubex Non-Skinning Butyl Sealant, manufactured at the Rubex facility, is a non-skinning, non-drying, self-healing synthetic rubber based sealant. It exhibits excellent adhesion even in adverse conditions, such as extreme temperatures and moisture levels. It does not string during application, and features outstanding cut-off and webbing characteristics. As a permanently flexible product, Rubex Non-Skinning Butyl Sealant maintains optimal tackiness and forms a long-lasting, acoustical, and resilient seal.

Product Uses: Rubex Non-Skinning Butyl Sealant is designed for use in the metal building industry as a sealant in standing seam manufacturing applications. It adheres well to Zinalume, KYNAR 500, Galvalume, and Galvalume Plus, as well as siliconized and polyvinyl flouride painted metals. Common applications include sealing: base track to slab, polyethylene barrier sheet overlaps, insulated panel top caps, and panel joints.

Technical Information:

Drying Time.....Non-Skinning	Water Penetration (ASTM E2140).....None
Color.....Off-White	Solids Content (ASTM C771-74).....Approx. 90%
Weight Per Gallon.....12.75 – 13.25	Low Temp. Flexibility.....No Adverse Effects
Extrudability.....200 g / 6 secs	Sag (ASTM D 2202).....0.2 in max
Application Temp. Range.....10°F – 120°F	Heat Aging.....No Effect
Service Temp. Range.....-60°F – 200°F	Flash Point.....110°F
Staining.....None	Shelf Life.....12 Months
Weatherability.....No Adverse Effects	Heat Aging.....No Adverse Effects
Vehicle Bleedout.....None After Three Weeks	Corrosive Properties.....None

Application Information: Ensure surfaces to be sealed are clean, dry, and free of oil and moisture. Exercise care during application to prevent air or contaminant entrapment. This product can be applied by standard hand or air-powered caulking guns. For bulk applications, use a Graco 55:1 ratio pump with fluid pressure of 40 to 50 psi. Once applied, do not handle, move, or pack for one hour. Panels bonded by this product can easily be separated for repair and maintenance, even after extended periods of time.

Packaging & Handling: Do not open until ready for use in order to maximize shelf life. Store at 60° – 80°F. Read all labeling before use. Rubex Non-Skinning Butyl Sealant is available in 10.1 and 30 oz. cartridges, as well as 1, 5, and 50 gallon containers.

Safety Instructions: CAUTION! This product contains mineral spirits, a combustible organic solvent. Keep away from heat, spark, and open flame. Avoid overexposure to vapors, as they may cause dizziness, nausea, and unconsciousness. Avoid exposure to skin and eyes. Consult Material Safety Data Sheet for further information.

Disclaimer: The information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site condition and other factors outside of Direct Metals Inc. or DMOI control are such that we assume no liability, nor make any warranty, express or implied for such information, recommendations or instructions related to the products under the Rubex Brand name or others. It is the users responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary.

Contact Us: For more information regarding this product and others, please contact us at :

DMOI
1800 Jim Neu Drive, Ste 3
Plymouth, IN 46563
Ph 574-935-3644

To find a distributor call:
Direct Metals Inc.
Ph 239-599-8527 or email
info@directmetalsinc.com