



#17-14 Econo Tapper

Designed for replacement of Stitch / Panel overlap fasteners into metal or wood substrates.

Features:

- #17 diameter for direct replacement of #12 or #14 (1/4-14) stitch/lap screws.
- Carbon Steel with Zinc plating and Corrosion resistant coating
- EPDM sealing washer for improved seal longevity

No predrill required for panels up to 24 ga, No predrill required for wood applications,

Predrill required for applications into red iron or steel purlins.

Specifications

Hex Drive, AB TH/Point

Torsional: 180 in-lbs

Tensile: 5300 lbs. min.

Shear: 3200 lbs min.

Pull out 12ga metal 1716 lbs ult

Pull out 24ga metal 261 lbs ult

Pull out 26ga metal 225 lbs ult

For wood installations test application assembly prior to use.

Thread Diameter: Maj: 0.295"
Min: 0.214"

Washer Diameter 7/16"

Selection

Sizes	Qty/Box	Part#	Head Style
#17 x 1"	2,500	DMI1063053	Cupped
#17 x 1"	2,000	DMI2A6041KJF	3/8 Hex w/BD washer
#17 x 1-1/2"	1,500	DMI2A6061KJF	3/8 Hex w/BD washer

Please note this fasteners is bagged in a standard 250 count.

Installation

Hex driver required. DMI suggests Mag drivers.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Suggested drill speed into most substrates is 1800 rpm.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Approximated values are average ultimate values. Values may change with strength and condition of substrate metal or wood.

Limitations: Not recommended for pressure treated wood substrates. Not recommended for aluminum or copper roofing panels. Not recommend for installation by impact drivers. Contact DMI for MSDS information

All sizes and color combinations may not be available for immediate shipment from all service centers.

To find a distributor call 855-800-8878 or visit www.directmetalsinc.com