

# Econo Wood to Wood Screw



## Features:

- Applications include 1" x 4" and other lumber attachment to wood substrate. Plywood decking to rafter, exterior deck construction, and concrete or or clay roofing tiles to wood deck substrates.
- Silver Dacro coating for corrosion resistance up to 500 hrs.
- #2 square drive for consistent driving performance

## Selection

<u>Available Sizes</u>	<u>Qty/Box</u>	<u>Part#</u>
#8 x 2-1/2"	2500	DMI4BPCDS08212
#8 x 3"	2000	DMI4BPCDS08300
#10 x 3-1/2"	1500	DMI4BPCDS10312
#10 x 4"	1000	DMI4BPCDS10400

#2 square drive suggested.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device. Suggested 1800 rpm.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Suggested 1" minimum penetration into substrate.

Made in Taiwan

**Limitations:** Not recommend for installation by impact drivers. Not recommended for pressure treated lumber. Contact DMI for MSDS information All sizes not available to ship from all Service Centers.

**To find a distributor call 855-800-8878 or visit [www.directmetalsinc.com](http://www.directmetalsinc.com)**