

#9 Wood to Wood Fastener



Features:

- #9 Diameter with deep root coarse thread for superior holding power into wood with convenient 250 pcs/bag packaging.
- Applications include 1" x 4" and other lumber attachment to wood substrate. Plywood decking to rafter, exterior deck construction, and concrete or clay roofing tiles to wood deck substrates.
- Safe for use in pressure treated lumber due to full green ACQ corrosion resistant coating.

Specifications

Green (ACQ) protective anti-corrosion coating double dip spin process.

Coating has been tested to surpass ASTM-B117 1000 hr test specifications.

Coating has been tested to surpass Kesternich DIN50018-2 OS test specifications for more than 15 cycles.

COO: Taiwan

Selection

<u>Available Sizes</u>	<u>Qty/Box</u>	<u>Part#</u>
#9 x 3"	1500	DMI4DA9300S2B

*Now bagged in 250
count bags.
Installation*

#2 square drive suggested.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device. Suggested 1800 rpm.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Suggested 1" minimum penetration into substrate.

Limitations: Not recommend for installation by impact drivers. Contact DMI for MSDS information
All sizes not available to ship from all Service Centers.

To find a distributor call 855-800-8878 or visit www.directmetalsinc.com