

# DEKFAST DEKPACK



## Features:

- Dekfast Commercial Roofing fasteners now available in “DEKPACK” 100 count boxes
- Fully coated with black E coat and FM approved
- Galvalume Stress Plates for insulation or membrane also available in “DEKPACK” 100 count boxes.

## Application:

- Designed for insulation attachment to wood and steel roof decks All Purpose / General Purpose fastening to wood and steel up to 18 ga.



## Specifications

### #12-13 Dekfast Screw

Torsional:	76 in-lbs
Tensile:	2,410 lbs. min.
Shear:	1,815 lbs min.
Pull out 22ga	513 lbs ult
Pull out 20ga	695 lbs ult
Pull out 18ga	787 lbs ult
Head Drive:	Phillips #3

Body Alloy: Carbon Steel, E Coat

COO: Taiwan

## Installation

0-2000 rpm electric screw gun with depth sensing nose piece or torque control device. Use PH3 bit tip.

## Selection

### #12-13 Dekfast All Purpose Screws

<u>Available Sizes</u>	<u>Qty/Box / Case</u>	<u>Part#</u>
#12 x 1-5/8"	100 / 900	DP158
#12 x 2-7/8"	100 / 900	DP278
#12 x 3-1/4"	100 / 900	DP314
#12 x 3-3/4"	100 / 900	DP334
#12 x 4-1/2"	100 / 900	DP412
#12 x 5"	100 / 900	DP500

### Stress Plates

<u>Available Sizes</u>	<u>Qty/Box / Case</u>	<u>Part#</u>
3" Insulation Round G	100 / 900	DPP3
2-3/8" Membrane Barbed G	50 / 450	DPP238

**Limitations:** Not recommend for installation by impact drivers.

Contact DMI for MSDS information

To find a distributor call 855-800-8878 or visit [www.directmetalsinc.com](http://www.directmetalsinc.com)