

PANCLIPSS 304 STAINLESS



Features:

- #10-9 full 304 stainless steel fastener has square #2 drive
- Thread designed to improve holding strength into plywood and MDF substrates vs our #10-12 fasteners.
- Miami-Dade county Approved Cert# L15-0209-01
- Applications include panel clip attachment to wood substrate, window installations into wood substrate.

Specifications

Torsional: 60 in-lbs
Pull out 3/4" PLY 520 lbs ult
Pull out 5/8" PLY 401 lbs ult
Pull out 1/2" PLY 344 lbs ult
Pull out 7/16" OSB 295 lbs ult
Coo: Taiwan

Ultimate values listed are the result of laboratory testing. Wood substrate strengths and availabilities vary by region and supplier. Specific job conditions should be considered and appropriate safety factors applied when specifying the proper fasteners.

Selection

<u>Available Sizes</u>	<u>Qty/Box</u>	<u>Part#</u>
<u>304SSDade County Approved Certification L 15-0209.01</u>		
#10 x 1" SQ2 TP17	5,000	DMIP31010D
#10 x 1-1/2" SQ2 T17	2,500	DMIP31015D
#10 x 2" SQ2 TP17	2,000	DMIP31020D

Installation

#2 square drive required.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Suggested drill speed is 1800 rpm.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Suggested 1" minimum penetration into substrate.

Limitations: Not recommend for installation by impact drivers.

Contact DMI for MSDS information