Polycarbonate Panel Accessories

POLYCARBONATE PANEL TO STEEL FBC FASTENER
Oversized #14 fasteners with an oversized 1.125" diameter washer. This fastener is for installation of polycarbonate panels to light to medium gauge metal substrate up to 8 ga steel to meet Florida Building Code Approval installation guidelines. Pre-drill of polycarbonate panel required.

Available Sizes	Qty/Box	Part#
1/4-14 x 1-1/2" SD3	750	DMI3PC112LW
250 PIECES PER BAG		
or by the piece		

POLYCARBONATE PANEL TO STEEL STAINLESS STEEL SCREW
Full 304 Stainless Steel protection with the added protection of DMG85 coating for resistance to dissimilar metal reactions in aluminum substrates. Special 3/4" diameter cupped style washer for standard applications to steel substrates. Pre-drill substrate and panel.

Available Sizes	Qty/Box	Part#
14 x 1-1/2" TPB 3/4C	1,000	DMIREPL14150SSB
14 x 2-1/2" TPB 3/4C	1,000	DMIREPL14250SSB
250 PIECES PER BAG		

POLYCARBONATE PANEL TO STEEL PANEL FBC FASTENER
#14 x 7/8" Stitch SD#1 fasteners with an oversized 1.125" diameter washer. This fastener is for installation of polycarbonate panels to light gauge metal panel overlaps up to 18 ga. Pre-drill of polycarbonate panel required.

Available Sizes	Qty/Box	Part#
1/4-14 x 7/8" SD1	750	DMI3PC078LW
250 PIECES PER BAG		
or by the piece		

POLYCARBONATE PANEL TO PC PANEL OR STEEL PANEL TO PC PANEL OVERLAP FASTENER - SS GROMMET SEAL
Stainless Steel 304 with EPDM grommet. Used for panel overlaps of polycarbonate and fiberglass panels. Hex head machine screw with rubber grommet that seals around top and bottom of panel penetrations. Predrill required for installation.

Sizes	Qty/Box	Part#
3/8" X 7/8"	Each	DMI23810PG
1/4" x 1"	2500	DMI210F100NWESN

POLYCARBONATE PANEL TO WOOD STAINLESS STEEL SCREW
Full 304 Stainless Steel protection with the added protection of DMG85 coating. Special 3/4" diameter cupped style washer for standard applications to wood substrates. Designed to meet DMI and Sunsky installation guidelines. Pre-drill of polycarbonate panel required.

Available Sizes	Qty/Box	Part#
14 x 1-1/2" TPA 3/4C	1,000	DMIREPL14150SSA
14 x 2-1/2" TPA 3/4C	1,000	DMIREPL14250SSA
250 PIECES PER BAG		

ECONO POLYCARBONATE PANEL TO WOOD FASTENER
Stainless Steel 304 no red rust construction. Includes 3/4" diameter stainless steel sealing washer to cover required predrill of polycarbonate panel. This fastener has not been approved by the factory and may void your poly warranty. However it is an economical alternative to the approved fastener above. Pre-drill of polycarbonate panel required.

Available Sizes	Qty/Box	Part#
#10 x 1-1/2" Mill	2,500	DMI4HSS150
250 PIECES PER BAG		

BUTYL*ROLL BUTYL TAPE SEALANT FOR PANEL SEALING
Available in various sizes supplied in ready-to-use rolls. For sealing gaps between polycarbonate panels and uneven metal panels around perimeter of skylights. Approved by DMI and Palram for use on MEGA, SUNSKY & SUNTUF panels.

| Available Sizes	Qty/Box	Part#
3/16 x 7/8" x 25' MTB	14	DMBT31678M
3/32 x 3/8" x 45' SB	40	DMBT3323845
3/32 x 1" x 45' SB	20	DMBT332145
3/16 x 2-1/2" x 20' TB	6	DMBT3162122

POLY-GLAZE™ PLUS CLEAR SILICONE SEALANT
SM5731 Poly-Glaze™ Plus Silicone is a one component, medium modulus, non-corrosive, neutral cure translucent silicone sealant. Primarily used to seal poly to poly and poly to steel panel joints. It has been tested and approved by DMI and Palram for use on MEGA, SUNSKY & SUNTUF panels.

| Available Sizes	Qty/Box	Part#
10.1oz tube Translucent	30	DMSM5731C

PVC Liner Panel Accessories

#10 PANCLIP LP WHITE LINER PANEL TO WOOD FASTENER
Panclip #2 square drive pancake head with full coat DMG85 1000 hr tested white coating. Panclip LP features a TP-17 point and low profile head. Clearance holes in PVC Panels may be required for approved installations.

Available Sizes	Qty/Box	Part#
#10 x 1"	5,000	DMIPD1010TW001
#10 x 1-1/2"	2,500	DMIPD1015TW001
#10 x 2"	2,000	DMIPD1020TW001
#10 x 2-1/2"	2,000	DMIPD1025TW001
#10 x 3"	1,500	DMIPD1030TW001

INDUSTRIAL PVC Panel Accessories

#14 STAINLESS STEEL TAPPING FASTENERS
Full 304 Stainless Steel construction with 3/4" diameter x 1/8" thick neoprene/SS bonded washer. 3/8" Hex drive available in Type A for light gauge and wood substrate applications and Type B for medium to heavy steel substrates (pre-drill required)

Available Sizes	Qty/Box	Part#
14 x 2-1/2" TPA	1,000	DMI4HHASS1425034
14 x 2-1/2" TPB	1,000	DMI4HHBSS1425034
250 PIECES PER BAG		