



DMI Razorback Ridgevent **HIBCO VV and other private label names.**

Installation guide for use with metal roofing ridge cap for FL4640-R1 , FL4640-R4, and 4640.3.

Installation

Each piece of 10'6" Ridge Cap will require 2 rolls of Razorback product.

1. Compile the needed materials in a safe and dry work environment. (Commonly the Razorback Ridgevent is adhered to the cap/flashing on the ground to create a vented ridge cap prior to roof loading)
2. Start the removal of the adhesive release paper by placing your thumb at the beginning of the adhesive strip (holding the adhesive against the razorback) and peel back the release paper. Use hand pressure to apply the pressure sensitive adhesive strip of the Razorback to the metal cap/flashing within 1/2" on the inside of the hem of the flashing.
3. Repeat step 2 for the opposite side of the ridge cap. You should now have Razorback on each side of the cap as shown in picture 3.
4. Immediately dispose of release paper in a safe fashion. Do not leave release paper on roofing surface.
5. Once roof loaded place the cap upside down so that the Razorback material is facing the metal panel. When necessary , cut the Razorback material with scissors or a utility knife for overlap of adjoining ventilated caps.
5. Install the metal flashing per panel manufacturers recommendations. Screw through the cap, through the center of the Razorback and through the panel high rib down through the substrate. Shown in picture 4.
6. When properly installed finished installation should look consistent. The material should appear to be compressed to fill all gaps between the Razorback Plus material and the panel or ridge cap. Shown in picture 5.

Safety

Based on current data, this product is not hazardous in the meaning of the Hazardous Material Regulations. Do not eat. We recommend that you take care, in use and disposal of this product. Make sure to dispose of adhesive release paper immediately after peeling, do not leave on roof surface.

Quick and easy, designed for original or retrofit installations



To find a distributor call 855-800-8878 or visit www.directmetalsinc.com