

#10 WOODZIP SCAMP SSC



WOODZIP S.C.A.M.P. 304 STAINLESS STEEL CAP HEAD

This little devil of a fastener is a true value as it provides the long life performance of our premium full stainless steel WoodZip SS fasteners on the head of the fastener at a lower price point. The SCAMP (Stainless Cap and Milled Point) is designed to provide the cut and hold performance of the WoodZIP fastener with the added corrosion protection of a 1/4" drive 304 series stainless steel head.



Features:

- 304 Stainless Capped Head that encapsulated the EPDM seal washer
- DMG85 coating system provides corrosion protection to meet various building code requirements
- Meets requirements of 2017 Florida Building Code R904.5.2
- Meets HVHZ ASTM TAS 114 appendix E , G85 Annex 5, 1000 hr exposed fastener requirements
- TP-17 Cut point allow speedy installation and reduces penetration shavings

Specifications

1/4 CHWH, TP-17 Point MTW

Torsional: 70 in-lbs
Tensile: 1,900 lbs. min.
Shear: 1,200 lbs min.

Tension/Pull-out testing

| #10 Pull out Substrate | #10 Pull out Ultimate Value |
|------------------------|-----------------------------|
| 1" x 4" SYP Pine | 999 lbs |
| 1/2" Plywood | 412 lbs |
| 3/4" Plywood | 587 lbs |

Values are ultimate values. Values may change with strength and condition of substrate wood.
ANSI/ASME B 18.6.1 COO: Taiwan

Selection

| Sizes | Qty/Box | Part# | Coating |
|--------------|---------|--------------|-------------------|
| #10 x 1" | 2,500 | DMI4SSC100M | DMG85 1000hr |
| #10 x 1-1/2" | 2,500 | DMI4SSC150M | DMG85 1000hr |
| #10 x 2" | 2,000 | DMI4SSC200M | DMG85 1000hr |
| #10 x 2-1/2" | 1,500 | DMI4SSC250M | DMG85 1000hr |
| #10 x 3" | 1,000 | DMI2CO488CAF | None, Zinc plated |

All above size are packaged 250 pieces per bag

Installation

1/4 Hex driver required for #10

LSC drivers are suggested.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Suggested drill speed in most substrates is 1800 rpm.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Suggested 1" minimum penetration into substrate.

Limitations: Not recommended for pressure treated wood substrates. Not recommended for copper or aluminum roofing panels. Not recommended for installation by impact drivers. Contact DMI for MSDS information

To find a distributor call 855-800-8878 or visit www.directmetalsinc.com