

#9 WOODZIP -SS-A



#9-15 WoodZIP-SS-A

Designed for the installation of aluminum roofing panels and aluminum liner panels to wood substrates. This fastener comes standard with a full DMG85 silver coating for additional protection from dissimilar metal reactions. This is one of our suggested fasteners for installation of metal roofing panels with-in 3000 Inft of salt water. Pilot holes must be pre-drilled and sealed prior to installation of the fastener.

- Full 304 Stainless Steel Construction
- DMG85 coating to combat dissimilar metal reactions.
- 12mm 304SS / EPDM Coated Washer
- Passes FBV HVHZ TAS 114, Appendix E and Miami Dade ASTM G85 Annex A 1000 hr exposed fastener corrosion resistance requirements. L 19-0219.01



MIAMI-DADE COUNTY LISTED

Specifications

1/4" HWH, Sharp Point

Torsional: 50 in-lbs

Double Shear: 2506 lbs ult.

Tension/Pull-out

Substrate	Ultimate Value
1" x 4" SYP Pine	542 lbs
1/2" Plywood	285 lbs
3/4" Plywood	466 lbs

Estimated values are ultimate values. Values may change with strength and condition of substrate wood.

DMI also suggest field tests prior to installation.

ANSI/ASME B 18.6.1

COO: Taiwan

Selection

Sizes	Color	Qty/Box	Part#
1"	Silver / Mill	2,500	DMI4HSS9100SA
1"	Bright White 014	2,500	DMI4HSS9100S014
1-1/2"	Silver / Mill	2,500	DMI4HSS9150SA
1-1/2"	Brite White 014	2,500	DMI4HSS9150S014
2"	Silver / Mill	2,000	DMI4HSS9200SA

Bagged 250 pieces per bag

Installation

1/4" Hex driver required, LSC drivers are suggested.

0-2000 rpm electric screw gun with depth sensing nose piece or torque control device.

Suggested drill speed in most substrates is 1800 rpm.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Suggested 1" minimum penetration into substrate.

Limitations: Not recommended for installation by impact drivers.

Contact DMI for MSDS information

To find a distributor call 855-800-8878 or visit www.directmetalsinc.com