

#14 PAN*CON SS Masonry Fastener

The Pan*Con SS is a Panclip low profile head fastener mated to a HILLO masonry thread. This fastener is suitable for installation into block or standard poured concrete (with predrill). The Hilo thread also self taps and secures into wood substrates.

Features:

- Full 410 Stainless Steel Construction
- DMG85 Silver coating covers the complete fastener. This fastener meets Florida Building Code corrosion resistance requirements FBC1506.6.
- DMG85 coating helps resist dissimilar metal reactions
- Low profile “non catch head” useful for concealed or low profile applications.



Specifications

Pullout and tensile values not available at time of publication. Please check with your salesperson for updated information if required prior to order.

Above values are average ultimate values. Values may change with strength and condition of substrate.

COO: Manufactured in Taiwan

Selection

<u>Standard Sizes</u>	<u>Qty/Box/Case</u>	<u>Part#</u>
#14 x 1-1/2"	100 / 1700	DMIPC41415T
#14 x 2-3/4"	100 / 1600	DMIPC414275T

<u>Special Order Sizes</u>	<u>Qty/Box/Case</u>	<u>Part#</u>
#14 x 4"	100 / 1200	DMIPC414400T
#14 x 6"	100 / 1200	DMIPC414600T

Installation

#2 square drive suggested.
 0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.
 Suggested 1" minimum penetration into substrate.
 Masonry Pre-Drill with 3/16" diameter drill bit.
 Predrill hole minimum of 1/2" deeper than fastener penetration.

Limitations: Not for use in areas subject to tide waters.