

TPO Bullet Boot

The Bullet Products solution for TPO flat roofing pipe penetrations. This flashing is made with white Polyolefin Elastomer (TPO) and can be heat welded to TPO roofing systems. The internal design improves water tightness with no caulking needed for installation. The boot is designed to be an aesthetically pleasing and features a removable pest screen.



Features & Benefits:

- Fast Installation
- 100% UV protected flexible TPO construction
- Non Staining and adapts to almost any roof pitch
- Covers the pipe inside and out
- Oil resistant
- Limited 35 year warranty

Selection

Bullet Weldable TPO Boots 12" Tall

<u>Sizes</u>	<u>Qty/Box</u>	<u>Part#</u>
1-1/2"	16	DMITPOBWT150
2"	16	DMITPOBWT200
3"	16	DMITPOBWT300
4"	8	DMITPOBWT400

Specifications

Tensile Strength: 1800 psi ASTM D412
Shore Hardness: 90 A ASTM D2240
Service Temp: -74 deg F to 190 deg F
Environmental Resistance: Excellent resistance to Ozone, UV, water, alcohol, weak acids & chlorine.

Installation

Limitations: There is no specific approval number or system manufactures warranty coverage on this item. Please check local building codes and roofing system manufacturers requirement prior to ordering.

To find a distributor call 855-800-8878 or visit www.directmetalsinc.com