

SCAMP Stainless Cap Head Metal Building Replacement Self Drilling Fasteners



Designed for the replacement of roofing and sidewall fasteners to steel substrates

- Replaces #10, #12, #14 or #17 self drilling screws without pre-drill
- Fastener designed to attach long-life metal roof panels such as GALVALUME that are used in pre-engineered metal building applications.
- 3/8" Capped 304 stainless steel provides lifetime protection against red rust on the head.
- Large and thick washer diameter to secure panels that may have some degradation at the fastening points.
- EPDM washer is protected by a 304 stainless steel washer guard
- 5/16" SCAMP diameter is one of the largest self drilling fasteners available with a long life head.



Specifications

| | |
|--------------------------|----------------------------|
| Fastener Size | : 5/16" x 1-1/4" |
| Washer Size | : 0.87" diameter |
| Point | : #3 |
| Drive | : 3/8" Hex |
| Shank Coating | : DMG85 |
| Shank Material | : C1022 Steel |
| Head Material | : 304 Stainless Steel |
| Washer Material | : 304 SS / E.P.D.M. Rubber |
| COO | : Taiwan |
| Drill and Tap Capability | : 0.036" to 0.210" Steel |

Selection

| <u>Available Sizes</u> | <u>Drill Point/HD</u> | <u>Qty/Box</u> | <u>Part#</u> |
|------------------------|-----------------------|----------------|-------------------|
| 5/16"-12 x 1-1/4" | SD3 3/8"H | 1,000 | DMI4SSCSD3516125M |



Installation

DMI 3/8" Hex Spring Clip Drivers Suggested
0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.
Do not over-drive or under-drive, not suggested for use with impact driver installation tools.

Limitations: Not recommend for installation by impact drivers. Contact DMI for MSDS information

To find a distributor of DMI products please visit www.directmetalsinc.com or call 855-800-8878