

# TIMBERTITE HEX TO WOOD



## TIMBERTITE HEX TO WOOD FASTENER

TimberTite screws are the all in one wood fastener. They are ideal for landscape walls, decks, post and beam construction, and more. No pre-drilling is necessary. These screws feature a 500 hour ceramic finish, perfect for use with pressure treated lumber. TimberTite screws are removable and reusable.

- Replaces spikes and rebar
- Perfect for landscape walls, decks, post and beam construction & more
- No pre-drilling required
- Removable and reusable
- 500 hour ceramic coat offers superior corrosion resistance
- Includes one 5/16 hex driver
- 3 Carded items per sellable unit
- 10 pieces per retail package



## Specifications

Steel Fastener with  
500 Hour Ceramic coating.

Designed for installation into  
dimensional wood substrates.

This fastener is threaded 2" from  
the point of the fastener. The rest  
of the length of the fastener  
would be smooth shank.

Pre-drilling for some extra dense/  
hard woods may be required.

DMI does not test applications or field  
conditions for this fastener as it may vary per  
application, and must be tested as an  
assembly.

## Selection

<u>Available Sizes</u>	<u>Qty/Box</u>	<u>Part#</u>
#14 x 2-1/2"	5,000	DMI3TTH14250
#14 x 4"	4,000	DMI3TTH14400
#14 x 6"	3,000	DMI3TTH14600
#14 x 8"	2,500	DMI3TTH14800
#14 x 10"	2,000	DMI3TTH14100

## Installation

5/16" Hex Driver

Do not overdrive or under drive, not suggested for use  
with impact driver installation tools.

*MSDS Based on current requirements of the occupational safety and health administration code, 26CFR, part 1910120 (Hazard communication), it has been determined that the product is considered "articles". A material safety data sheet is not required for items meeting the code definition of "article". Installation guide available upon request.*