

#14 PAN*CON SS Masonry Fastener

The Pan*Con SS is a Panclip low profile head fastener mated to a HILO masonry thread. This fastener is suitable for installation into block or standard poured concrete (with predrill). The Hilo thread also self taps and secures into wood substrates.



Features:

- Full 410 Stainless Steel Construction
- DMG85 Silver coating covers the complete fastener. This fastener meets Florida Building Code corrosion resistance requirements FBC1506.6 and TAS 114, Appendix E (ASTM G85 Annex A5).
- DMG85 coating helps resist dissimilar metal reactions.
- Low profile “non catch head” useful for concealed or low profile applications.
- Miami-Dade County Listing # L 19-0219.03

Specifications

Pullout and tensile values not available at time of publication.

Corrosion resistance ASTM G85 Annex A5/TAS 114 Appendix E, 0% corrosion.

Double shear Strength: 5722 lbs

Above values are average ultimate values. Values may change with strength and condition of substrate.

COO: Manufactured in Taiwan

Selection

<u>Standard Sizes</u>	<u>Qty/Box/Case</u>	<u>Part#</u>
#14 x 1-1/2"	100 / 1700	DMIPC41415T
#14 x 2-3/4"	100 / 1600	DMIPC414275T

<u>Special Order Sizes</u>	<u>Qty/Box/Case</u>	<u>Part#</u>
#14 x 4"	100 / 1200	DMIPC414400T
#14 x 6"	100 / 1200	DMIPC414600T

Installation

#2 square drive suggested.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Suggested 1" minimum penetration into substrate.

Masonry Pre-Drill with 3/16" diameter drill bit.

Predrill hole minimum of 1/2" deeper than fastener penetration. Clean hole before install.

Limitations: Not for use in areas subject to tide waters.