

#12 PanclipSS XLP MTW Fastener



Features:

- Panclip XLP Extra Low profile pancake/wafer head designed for Nail Strip panel installation eliminating head marks you might find with a taller pancake head.
- #12 diameter and deep root thread provide exceptional holding power into particle board, plywood and OSB substrates vs. standard #10 pancake head fasteners.
- Full 304 Stainless Steel construction for a high level of corrosion resistance.
- DMG85 Silver coating covers the complete fastener to reduce the risk of dis-similar metal reactions with aluminum.
- The XLP meets Florida Building Code corrosion resistance requirements (FBC1506.6)



Specifications

#12-8 x (L) SQ2 Drive S Point

Tensile Strength: 2003 lbs ult

Torsional: 60 in-lbs

Shear: 1860 lbs ult

Pull out / Withdrawal :

Plywood 3/4" 587 lbs ult

Plywood 5/8" 446 lbs ult

Plywood 1/2" 395 lbs ult

OSB 23/32" 520 lbs ult

Above values are average ultimate values. Values may change with strength and condition of substrate wood.

Tested values are on carbon steel screw variant.

Selection

<u>Sizes</u>	<u>Qty/Box</u>	<u>Part#</u>
#12 x 1"	5,000	DMIPXLP121SS
#12 x 1-1/2"	2,500	DMIPXLP1215SS
#12 x 2-1/2"	1,500	DMIPXLP1225SS

Installation

#2 square drive suggested.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Suggested 1" minimum penetration into substrate.

COO: Manufactured in Taiwan

Limitations: Not recommended for installation by impact drivers.