#14 PANCLIP-SD-L Fastener

- #14-13 fastener has a low profile pancake head designed for roofing clip and insulated panel installation into wood or light gauge steel deck up to 16 ga thickness.
- DMG85 Black coating covers the complete fastener.
 This fastener meets Florida Building Code corrosion resistance requirements (FBC1506.6) and 1-1/2" has a Miami-Dade
 County P.C Listing # L 16-0706.02 for corrosion resistance.
- Panel clip/Plywood/Nailboard/Fixture attachment and more...







Specifications

Torsional: 110 in-lbs

Pull out SPF Wood 1" penetration

995 lbs ult

Pull out 3/4" PLY 630 lbs ult

Pull out 22 ga E 575 lbs ult

Pull out 16 ga 1103 lbs ult

Head Height .090" - .010"

Head Diameter: .490" - .510"

Thread Diameter: Maj: .238" Min .180"

Above values are average ultimate values. Values may change with strength and condition of substrate wood. Not for use with pressure treated ACQ or MCQ lumber. 410 Stainless Steel parts available or pressure treated lumber applications.

COO: Taiwan

Selection

<u>Sizes</u>	Qty/Box	Part#	M/D Listing #
#14 x 1-1/2"	2500	DMIPL1415D	L 16-0706.03
#14 x 3"	2000	DMIPL1430D	
#14 x 4"	1000	DMIPL1440D	
#14 x 5"	1000	DMIPL1450D	
#14 x 6"	1000	DMIPL1460D	
#14 x 7"	1000	DMIPL1470D	
#14 x 8"	1000	DMIPL1480D	

3" and 4" lengths are fully threaded otherwise 4" of thread under the head.

Installation

#2 square drive suggested.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device. Suggested 1800 rpm.

Do not overdrive or under drive, not suggested for use with impact driver installation tools. Suggested 1" minimum penetration into substrate.

Contact DMI or pictorial washer seating guide.

Limitations: Not recommended for pressure treated wood substrates. Not recommended for copper roofing panels. Not recommend for installation by impact drivers. Contact DMI for MSDS information