#9-15 Woodgrip MTW


#9-15 WOODGRIP™ CONTROL SEAL

The original Woodgrip for metal roofing installation to wood substrates, also popular for ridge vent installation to wood substrates. Assembled with bell guard EPDM control seal washer and plated and coated with multi-layer corrosion resistance. 1/4" HWH and sharp point. Packaged 250 pieces per bag. Available to be painted to match all DMI colors.

Features:

High hex washer head provides driving stability
Assembled with Control Seal washer for consistent tight seal
VistaCoat coating provides multiple layers of corrosion protection
Sharp point for penetrating sheet metal panels
Bell guard two piece washer seals on multiple angles





Specifications

1/4" HWH, Sharp Point

Torsional: 60 in-lbs

Tensile: 1,751 lbs. min.

Shear: 1,223 lbs min.

Pull out SYP Wood 1" penetration

Southern Yellow Pine 748 lbs ult

Pull Over 26 ga: 637 lbs ult

Pull Over 29 ga: 577 lbs ult

Thread Diameter: Maj: .181" Min .127"

Painted, Coated, Packaged in the U.S.A., may contain components manufactured in Taiwan.

Selection

Available Sizes	Qty/Box	Part#
#9 x 1"	3,000	DMI2V0161CCF
#9 x 1-1/2"	2,500	DMI2V0261CCF
#9 x 2"	2,000	DMI2V0381CCF
#9 x 2-1/2"	1,500	DMI2V0461CCF
#9 x 3"	1,000	DMI2V0485CCF

Installation

1/4" Hex drive required, LSC spring clip suggested.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Suggested drill speed is most substrates is 1800 rpm.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Suggested 1" minimum penetration into substrate.

Approximated values are average ultimate values.

Values may change with strength and condition

of substrate wood.

Limitations: Not recommended for pressure treated wood substrates. Not recommended for aluminum or copper roofing panels. Not recommend for installation by impact drivers.

Contact DMI for MSDS information