



PanclipSS XLP MTW Fastener

Features:

- Panclip XLP Extra Low profile pancake/wafer head designed for Nail Strip panel installation eliminating head marks you might find with a taller pancake head.
- #12 diameter and deep root thread provide exceptional holding power into particle board, plywood and OSB substrates vs. standard #10 pancake head fasteners.
- #12 diameter screw has SQ#2/PH#2 drive.
- Full 304 stainless steel construction for highly corrosive environments.

Specifications

#12-8 with "DMI3" Headmark
 Tensile Strength: 1508 lbs ult
 Torsional: 50 in-lbs
 Shear: 1460 lbs ult
 Pull out :

Plywood	3/4"	587 lbs ult
Plywood	5/8"	446 lbs ult
Plywood	1/2"	395 lbs ult
OSB	23/32"	520 lbs ult

Above values are average ultimate values. Pullout testing was done on carbon steel coated parts and may vary from the above average values. Values may change with strength and condition of substrate wood. 304 Stainless Steel parts are approved for pressure treated lumber applications.

COO: Manufactured in Taiwan

Selection

<u>Available Sizes</u>	<u>Qty/Box</u>	<u>Part#</u>
#12 x 1"	5,000	DMIPXLP121SS
#12 x 1-1/2"	2,500	DMIPXLP1215SS

Installation

#2 square drive suggested.
 0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.
 Do not overdrive or under drive, not suggested for use with impact driver installation tools.
 Suggested 1" minimum penetration into substrate.



Limitations: Not recommended for installation by impact drivers. 040315