

#14 ZAC Washered Masonry Anchor



ZAC® Anchors



3/8" HWH termination fastener
For fastening termination bar at wall terminations

- Term bar fastener that can be backed out.
- Threads into wood, masonry, concrete and metal.
- ZAC cap is zinc aluminum composition and will never red rust.
- Can be removed and re-engaged for roof repairs without damage to the roof system.
- e-coat coating on thread.

Application

ZAC Anchor

Use with:
Wood, masonry, concrete,
and steel at roof wall terminations.



Head: 3/8" AF ZAC HWH Long Life
Dia: #14 (.248)

Notes

Dimensions are nominal and in inches unless noted. The specific job conditions should be considered and appropriate safety factors applied when specifying the proper fasteners.

Performance Load Capacities (2000 psi concrete)

Pre-Drill	7/32"	7/32"	7/32"
Embed. Depth	1"	1.25"	1.375"
Tension Load (lbs)	620	810	905
Shear Load (lbs)	830	1130	1280

Notes: All load values listed are ultimate load capacities and are not allowable load capacities. These loads should be reduced by an appropriate safety factor of at least 4 to determine the allowable load.

Selection

Dia and Length	Material No.	North American Code	Carton Wt. (lbs)	Carton Qty.	Skid Qty.
#14 x 1-3/8" HWH ZAC Anchor	792897	ZA-#14x1-3/8-HW3/8-N-E0999-C	25	1000	60,000

Notes: Load capacity is related to embedment depth. Select anchor length to provide needed embedment depth for the installed anchor.

Installation

Tools: Carbide-tipped masonry drill bit sized slightly larger than nominal diameter to allow clearance.

Limitations: Not recommend for installation by impact drivers. Contact DMI for MSDS information

Sales are done through DMI registered distributor network only please contact 855-800-8878 to find a registered distributor or email distributors@directmetalsinc.com