

# ZAC Stitch / Lap Fastener



## Features:

- ZAC , uniform ZINC Alloy Cap head the withstands the toughest installation conditions.
- Lifetime limited warranty/ guarantee against red rust corrosion on the head of the fastener.

## Application:

- Designed for metal panel to panel stitch/panel overlap applications, .030" - .095" thick Steel



## Specifications

Torsional: 150 in-lbs  
Tensile: 3,800 lbs. min.  
Shear: 2,850 lbs min.

Pull out 22ga 379 lbs ult

Pull out 24ga 304 lbs ult

Pull out 26ga 204 lbs ult

Head Diameter: .650"

Thread Diameter: Maj: .246" Min .185"

Painted Fasteners BAP

Available in 3/8" or 5/16" AFH HWH

5/16" is standard unless specified.

## Selection

<u>Available Sizes</u>	<u>Qty/Box</u>	<u>Part#</u>
1/4-14 x 7/8" SD1 5/16" AFH	2,000	DMI2S5031FMF
1/4-14 x 7/8" SD1 3/8" AFH	2,000	DMI2S5065FMF

## Installation

DMI Spring Clip Drivers Suggested

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Suggested drill speed is most substrates is 1800 rpm.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Approximated values are average ultimate values.  
Values may change with strength and condition of substrate wood.

**Limitations:** Not recommend for installation by impact drivers.

Contact DMI for MSDS information