

Termination Bar is manufactured from specially extruded aluminum bar for wall termination applications. DMI / Dekfast™ termination bar has reinforced strengthening ribs that allow for use in high wind areas.


RIBBED TERMINATION BAR WITH LIP (KICK)

Dimensions: 0.050" edge x 0.075" ribs x 1" wide x 10' long
Holes: 0.268" x 0.380" slotted at 6" on center standard
For use with: #14 Dekfast HD, #15 Dekfast, ZAC Anchor, Zinc Nailin, and Dekspike.
500 LNFT / Tube (50 pieces x 10') Part# DMI2H3035



RIBBED TERMINATION BAR FLAT

Dimensions: 0.075" edge x 0.100" ribs x 1" wide x 10' long
Holes: 0.268" x 0.380" slotted at 6" on center standard
For use with: #14 Dekfast HD, #15 Dekfast, ZAC Anchor, Zinc Nailin, and Dekspike.
500 LNFT / Tube (50 pieces x 10') Part# DMI2H3125



LIP & BALL TERMINATION BAR (NO RIBS)

Dimensions: 0.088" edge x 1" wide x 10' long
Holes: 0.268" x 0.380" slotted at 6" on center standard
For use with: #14 Dekfast HD, #15 Dekfast, ZAC Anchor, Zinc Nailin, and Dekspike.
500 LNFT / Tube (50 pieces x 10') Part# DMI2H3155



NAILIN - DRIVE PIN MASONRY ANCHORS

Termination bar fastener designed for installation into concrete, block, brick and stone. Zinc composition to prevent corrosion with zinc plated nail/pin. Stainless steel nailin anchors have a 304 stainless steel pin with the same zinc body to resist corrosion. Pre-drill and hammer pin for installation.

<u>Zinc Pin Sizes</u>	<u>Qty/Box</u>	<u>Part#</u>
1/4" x 1"	100/1,000	DMI4N7100
1/4" x 1-1/4"	100/1,000	DMI4N7110
1/4" x 1-1/2"	100/1,000	DMI4N7115
1/4" x 2"	100/1,000	DMI4N7120
1/4" x 3"	100/Box	DMI4N7130

<u>Stainless Steel Pin Sizes</u>	<u>Part#</u>
1/4" x 1-1/4"	100/1000 DMI4N7112

Zinc Nailin Anchor performance in 4000 psi concrete:
7/8" Embedment depth; tension load : 820, shear load : 1500.
1-3/8" Embedment depth; tension load : 1150, shear load : 1500.




#14 ZAC™ ANCHOR LONG LIFE TERM BAR ANCHOR w/washer

Termination bar fastener that can be backed out. Threads into wood, masonry, concrete and light gauge metal. ZAC™ cap is zinc alloy that is designed to never rust with a 20 year warranty. Can be removed and re-engaged for roof repairs without damage to the roof system. Shank is coated with black e-coating for corrosion protection.

3/8" AFH ZAC Anchor performance: **7/32" Drill bit required for pre-drill**
1" Embedment depth, tension load : 620, shear load : 830.
1-1/2" Embedment depth, tension load : 1000, shear load : 1430.

<u>Available Sizes</u>	<u>Qty/Box</u>	<u>Part#</u>
#14 x 1-3/8"	1,000	DMI2N7305FM999C



STEEL DECKING & UL DECKING ATTACHMENT FASTENERS

Used for attachment of steel decking to steel purlins from 12ga up to 1/2" thick. #10 x 3/4" designed for steel B deck side lap stitch. The original TEK screw with a worldwide reputation for fast drilling quality self drilling points for metal to metal applications with FM & ICC listings/approvals. TEKS featured here have a full Climacoat 1000 hour+ coating. Most sizes are Made in the USA. Full box orders only.

<u>Available Sizes</u>	<u>Qty/Box</u>	<u>Part#</u>
#12-24 x 1-1/4" TEK5 HWH	2,500	DMI1006053
#12-24 x 1-1/2" TEK5 HWH	2,000	DMI1070053
1/4-14 x 3" TEK3 HWH	1,000	DMI1157000
1/4-28 x 3" TEK5 HWH	1,000	DMI1074000
1/4-28 x 4" TEK5 HWH	500	DMI1075000
1/4-28 x 5" TEK5 HWH	250	DMI1641000
1/4-28 x 6" TEK5 HWH	250	DMI1431000
1/4-28 x 8" TEK5 HWH	150	DMI1590000
#10-16 x 3/4" TEK1 HWH	5,000	DMI1107053



<u>Pull out 1/4-28 TEK5 Steel</u>	<u>Pull out 12-24 TEK5Steel</u>	<u>Made in the USA #12-24</u>
12GA: 1507	12: 1507	Shear: 2762
3/16: 3300	3/16: 3107	Tensile: 3020
1/4: 5059	1/4: 3999	Torsional: 100 inlbs

**SEE PAGE 22
FOR MORE
DECKING
FASTENER
OPTIONS**

