

DMI Utility Walk Doors



3100 Series Door

The 3100 series door has been designed for steel, masonry and wood construction and has been tested to surpass Florida Building Code standards for non-HV Zones. These prehung 4-way universal swing individually boxed doors recorded +55.00/-66.7 psf pressures in FBC wind testing (FL 7648.1).

1-3/4" thick door panel pressure injected with 2.2 pounds of polyurethane foam per cubic foot. This embossed white steel panel provides an R-12 insulation value. Rolled edge door panel design that is pre-painted with two coats of polyester paint for a durable and long lasting finish. The door is prehung mounted to the frame by three 12-gauge steel Zinc plated, 4 1/2" x 4" fixed pin hinges.

Availability: 3/0 x 6/8 Solid White Part# DAJ31057

Packaged 10 doors/pallet

Options: 9 lite interior grid windows that are foamed in place, special order #DAJ310679L. Lock sets sold separately.



Standard door



Nine Lite
22x36
(no-grid one lite available)

1-3/4" thick door pressure injected with a polyurethane foam core with an R-12 insulating value

Heavy extruded aluminum reinforcing for lock set

Aluminum stile of door is reinforced for added strength

Aluminum Frame

Polyurethane foam core guaranteed not to swell, delaminate or warp

Door is prepped for lockset by boring a 2-1/8" diameter hole at a 2-3/4" backset with a 1" edge bore

Flush design-rolled edges for style, strength and corrosion resistance

Top and bottom sill sweeps are fabricated of a dual durometer vinyl consisting of three flexible wands and rigid base

Aluminum 1/2" Code Approved Low Profile Threshold

To purchase: Direct Metals Inc offers our product through our registered distributors and wholesalers, to find a distributor please call 855-800-8878 or visit www.directmetalsinc.com for product information.