

DMI Razorback Ridgevent for ventilation of metal roofing ridge cap



Razorback Ridgevent is a long life universal ridge vent roll for ventilation of metal roofing panel systems. Quick and easy installation with hot melt adhesive strips. Convuluted foam with UV inhibitor coating designed to fit most metal roofing panel profiles. Used to close the gap between ridge or hip cap and metal roofing panels.

Features:

- Inexpensive, quick and easy to install
- Designed for many roof panel configurations and pitches from 2/12 to 20/12
- Low profile attractive installed appearance
- Does not scratch painted metal surfaces
- This product has a Florida Building Code Product Approval number *



* Razorback Ridgevent is manufactured and private labeled for DMI and the Florida Building Code approval is registered under that manufacturers product name. All sales as of 3/15/19 have no actual or implied warranty.

Specifications

Test	Standard	Result
100 MPH Wind D R	TAS100	Passes
	CRL 6875	Passed
Net Free Area	3/4" Rib Panel	17 Sq inch per , ridge lft
Air Permeability	ASTM D737	840 cu ft / min
Attic Dust	ASTM D1739-98	No Clogging
Abrasion	ASTM D1175	No Damage

All test data above provided by the private label manufacturer.

Sizing Suggestions

A minimum of 25% compression suggested

1-1/2" Tall for 5V Crimp, 3/4" high rib, 1" snaplock and corrugated panels with a major rib height of 1" or less.

1-3/4" Tall for R/PBR Panel or metal roofing corrugated panels with major rib of 1.4" or less.

Selection

Available Sizes	Qty/Box	Part#
1-1/2" x 2" x 10'	10	DMIRB1122010
1-3/4" x 2" x 10'	10	DMIRB1342010

Safety

Based on current data, this product is not hazardous in the meaning of the Hazardous Material Regulations. Do not eat. We recommend that you take care, in use and disposal of this product. Make sure to dispose of adhesive release paper immediately after peeling, do not leave on roof surface.

Installation

Peel back adhesive release paper beyond the length of product you need. Adhere adhesive side to metal flashing/ clean surface.

Immediately dispose of release paper in a safe fashion. Do not leave release paper on roofing surface.

Install the metal flashing per panel manufacturers recommendations.

When allowable per panel manufacturers specifications install fasteners through the flashing and through the center of the Razorback product into the substrate.

Quick and easy, designed for original or retrofit installations



To find a distributor call 855-800-8878 or visit www.directmetalsinc.com