



**#14-10 410 STAINLESS STEEL DEKFAST™ HD**

Ideal for insulation or membrane attachment to wood and light gauge steel in a corrosive environment. Also used for standing seam metal roof clip installation with clips with fastener relief. #3 Phillips drive with SD#1 point that cuts through gravel and BUR and metal up to 18ga. 410 stainless steel fasteners provide fair resistance to corrosion in mild to light industrial environments. 410 SS is a magnetic heat-treatable stainless steel that exceeds the Factory Mutual corrosion-resistance standard 4470. Use DEKFAST stress plates, termination and batten bar.



Available Sizes	Qty/Box	Part#
#14 x 1-1/2" PH#3	1,000	DMI2G8500B
#14 x 2" PH#3	1,000	DMI2G8510B
#14 x 3" PH#3	1,000	DMI2G8520B
#14 x 4" PH#3	1,000	DMI2G8530B
#14 x 5" PH#3	1,000	DMI2G8540B
#14 x 6" PH#3	1,000	DMI2G8550B
#14 x 7" PH#3	500	DMI2G8560B *
#14 x 8" PH#3	500	DMI2G8570B *
#14 x 10" PH#3	500	DMI2G8580B *
#14 x 12" PH#3	500	DMI2G8590B *

\* Lengths greater than 6" may require additional lead time and minimums.

#14 410 SS DEKFAST HD fasteners come packaged in plastic reusable pails. Each pail includes one PH3 installation bit.

Pull out Steel	Pull out Wood	Size PH3
22GA:470		HeadH .118
20GA:635	3/4"PLY:495	HeadD .440
18GA:815	MTH Head	Thread: .235

Available for order in full box quantity only.

**Limitations:** Not recommend for installation by impact drivers. Contact DMI for MSDS information

Sales are done through DMI registered distributor network only please contact 855-800-8878 to find a registered distributor or email [distributors@directmetalsinc.com](mailto:distributors@directmetalsinc.com)