




ProfileVent metal roofing ridge vent rolls

ProfileVent is a roll out single layer ridge vent. It is a strong, durable, modified polyester, non-woven, UV stable, non-wicking, fiber based matting designed for use with metal roofing metal roofing ridge ventilation system designed for roof pitches from 2:12 to 20:12. ProfileVent is custom cut to fit the individual panel profiles. ProfileVent's compatibility with a steep roof pitch makes it uniquely suitable for these applications, without sacrificing ventilation performance. Maintain the ridge line appearance without the need to raise the ridge cap to accommodate the vent. ProfileVent is made in the U.S.A. and is Dade County approved for metal roofing ridge ventilation applications.

Application:

Metal roof ventilation between metal ridge cap and panel.



Features:

- Fits under any ridge cap, available in roll or 3' sticks (select profiles)
- Won't crack or rust during shipping or installation
- Adhesive dabs in profile cuts to help prevent slippage during installation
- 40 profiles to find your specific panel profile
- Miami-Dade Product control approval 12-0724.3, when ridge cap is secured with #14 x 2" Woodgrip TP17 screws.

Specifications

TEST	STANDARD	RESULT
Cold crack test	private	passed
Attic dust test	ASTM D1739 -98	passed
Wind driven rain infiltration	TAS 100	passed
Simulated snow infiltration	Private	passed 70 mph for 5 mins
Dust exposure clogging	ICBO AC132 section 5.2	passed
Net free area ventilation	Private	17 in 2/ft
Warranty	Limited	
Country of Origin	Made in U.S.A.	
N.A.F.T.A. Content 100%		

Size Selection

Roll Profiles	Qty/Pkg	Part#
5V Crimp	100Inft	DMI2T1282PV
R/PBR	100Inft	DMI2T0679PV
3/4" RIB	100Inft	DMI2T0900PV
2.67CORR x 7/8"	100Inft	DMI2T0120PV
1" NailStripSS 16"OC	100Inft	DMI2T1564PV
1-1/2" SL SS 16" OC	100Inft	DMI2T1639PV
1-3/4" SL SS 16" OC	100Inft	DMI2T1606PV
1-3/4" SL SS 18" OC	100Inft	DMI2T1628PV
3' Stick Profiles	Qty/Pkg	Part#
R/PBR	24	DMI2T0679PV3
3/4" RIB	24	DMI2T0900PV3

Ridge Anchor Clips

Available for order : ask your sales person for details on suggested installations and requirements.

MSDS information: **Section I:** MSDS #04002K1 category non woven coated abrasive **Section II Hazardous Components :** None
Section III Physical Data: % volatiles by volume 3-4, physical state: solid **Section IV,** Fire and explosion hazard data: flash point :N/A, extinguishing media: water, CO2, foam **Section V Health hazard information:** possible skin irritation from prolonged contact, may cause irritation to eyes **Section VI Emergency first aid procedures:** Skin contact , rinse with water Eye contact, rinse with water for 15 minutes. Seek medical attention. Ingestion, give water. Seek medical attention. **Section VII Spill & leak procedures:** Clean up and dispose of in accordance to applicable laws. Recommended disposal incinerate and or landfill. **Section VIII Special protection information:** protective gloves and eye protection as desired by user, local ventilation **Section IX Special precautions:** none/ use good house keeping
Section X Regulatory information: U.S. Federal regulations - none, California Prop 5 - no materials present required reporting
Section XI Shipping information: Hazard class not required by DOT, ID number none, marine pollutant no, hazard substance none

Disclaimer: The information contained within is based on information available to us, and is believed to be accurate. Health and safety precautions in this MSDS may not be adequate for all individuals and product uses. Installation guide available upon request.

TO FIND A DISTRIBUTOR CALL 855-800-8878

WWW.DIRECTMETALSINC.COM