

# #12 Panclip XLP MTW Fastener

## Features:

- Panclip XLP Extra Low profile pancake/wafer head designed for Nail Strip panel installation eliminating head marks you might find with a taller pancake head.
- #12 diameter and deep root thread provide exceptional holding power into particle board, plywood and OSB substrates vs. standard #10 pancake head fasteners.
- DMG85 Silver coating covers the complete fastener.
- The XLP meets Florida Building Code corrosion resistance requirements (FBC1506.6) and has a Miami-Dade County P.C Listing # L 21-0630.04 certifying corrosion resistance.



## Specifications

#12-8 x (L) SQ2 Drive SPoint

Tensile Strength: 2003 lbs ult

Torsional: 60 in-lbs

Shear: 1860 lbs ult

Pull out :

Plywood 3/4" 587 lbs ult

Plywood 5/8" 446 lbs ult

Plywood 1/2" 395 lbs ult

OSB 23/32" 520 lbs ult

Above values are average ultimate values. Values may change with strength and condition of substrate wood. Not for use with pressure treated ACQ lumber. 304 Stainless Steel parts available or pressure treated lumber applications.

## Selection

<u>Sizes</u>	<u>Qty/Box</u>	<u>Part#</u>	<u>M/D Listing #</u>
#12 x 1"	5,000	DMIPXLP121D	L 21-0630.04
#12 x 1-1/2"	5,000	DMIPXLP1215SD	L 21-0630.04
#12 x 2-1/2"		Coming in late 2022	

## Installation

#2 square drive suggested.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Suggested 1" minimum penetration into substrate.

COO: Manufactured in Taiwan

**Limitations:** Not recommended for installation by impact drivers. Not for use with Aluminum or Copper metal panels (See 304 SS parts). Not for use with pressure treated ACQ lumber.