

#10 Direct*Seal SS



Direct*Seal SS Woodbinder with Uniseal Head Full 304 Stainless Woodscrew

Full 304 Stainless Steel head and body with one piece washer shroud. Designed to install metal roof and metal wall panels to wood substrates such as post frame building construction and sheeting.

1/4" HWH head provides driving stability

Assembled with a quality EPDM rubber washer.

Predrilling of fastener is required to install through galvanized or galvalume sheets. Predrilling and sealing is also suggested light gage stainless or aluminum panels.



PERFORMANCE POUNDS ULTIMATE

#10 304 Stainless Steel ST Direct*Seal Woodbinder Woodscrew, Made in Taiwan

PULL OUT WOOD SPRUCE, PINE	PULL OUT PLYWOOD	PULL OUT OSB
1 1/2" PENETRATION : 1176	3/4" : 616	
1" PENETRATION : 678	1/2" : 312	7/16": 208

AVAILABLE SIZES:

#10-15 w/seal washer 1/4" Hex Drive

Size	Qty/Box	Part#
1"	3,000	DMI3DSFS100M
1-1/2"	2,500	DMI3DSFS115M
2"	2,000	DMI3DSFS120M
3"	1,000	DMI3DSFS130M

INSTALLATION:

TOOLS: 0 – 2000 RPM screw driver equipped with depth sensing nose piece, Min 6 amp DMI Long Spring Clip 1/4" driver suggested for installation, purchased separately.

Limitations: Not recommended for installation by impact drivers. Contact ST for MSDS information
If used with aluminum panels predrilling, cleaning and sealing of holes is suggested. Check with your panel supplier for suitability or compatibility with your panel.

To find a distributor call 855-800-8878 or visit www.directmetalsinc.com