



# Panclip SD MTM Fastener

### Features:

- Panclip-SD Low profile pancake for panel clip installation into metal substrates
- Additional uses include fastening of articles to steel tube when a low profile head is required.
- Zinc plated plus additional 1000 hr coating tested to exceed ASTM B117 and FBC 1506.5 corrosion resistance standards.
- Square Drive available for driving stability and driver strip-out resistance

## #10-16 Specifications

Tensile Strength: 1900 lbs ult

Torsional: 76 in-lbs

Shear: (14 ga) 1448 lbs ult

Pull out :

12 ga 1400 lbs ult

14 ga 860 lbs ult

16 ga 579 lbs ult

18 ga 423 lbs ult

22 ga 216 lbs ult

Above values are average ultimate values. Values may change with strength and condition of substrate.

#2 square driver is used for installation.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

SD2/3 Suggested for metal substrates up to 8 ga.

## Selection

### SD2 drill up to 8 ga steel

Available Sizes	Qty/Box	Part#
#10-16 x 1" SQ2 SD2	5,000	DMIPD210100C
#10-16 x 1-1/2" SQ2 SD2	2,500	DMIPD210150C

### SD2 drill up to 6 ga steel

#12-14 x 1" SQ2 SD3	2,500	DMIPD312100C
#12-14 x 2" SD2 SD3	2,000	DMIPD312200C

### SD4 HD drill up to 1/4"(.250) steel

1/4-20 x 1-1/2" SQ3 SD4	2,500	DMIP514150TC
1/4-20 x 5" SQ3 SD4	1,000	DMIP514500TC
1/4-20 x 7" SQ3 SD4	1,000	DMIP514700TC

Some sizes are also available in 410 stainless steel with additional Dade County approved coating for higher levels of corrosion resistance.

**Limitations:** Not recommended for use with aluminum or copper roofing panels. Not recommend for installation by impact drivers. Contact DMI for MSDS information Contact DMI at 855-800-8878 with questions.