

PANCLIP-SD-SS-L Fastener



Features:

- #14-13 fastener has square #2 drive
- Applications include panel clip/Plywood/Nailboard attachment to wood and up to 16ga metal decking.
- Full 410 Stainless Steel construction with DMG85 Silver Longlife and dissimilar metal protective coating.
- DMG85 coating has been tested to surpass Florida Building

Code requirements of FBC 1506.6, ASTM TAS 114 Appendix E and ASTM G85 Annex 5.

Specifications

Torsional: 110 in-lbs
Pull out SPF Wood 1" penetration
995 lbs ult
Pull out 3/4" PLY 630 lbs ult
Pull out 22 ga E 575 lbs ult
Pull out 16 ga 1103 lbs ult

Head Height .090" - .010"

Head Diameter: .490" - .510"

Thread Diameter: Maj: .238" Min .180"

Above values are average ultimate values. Values may change with strength and condition of substrate wood. Values are based on carbon steel Panclip SDL test results COO: Taiwan

Selection

Available Sizes	Qty/Box	Part#
#14 x 1-1/2"	2500	DMIP41415D
#14 x 3"	1000	DMIP41430D
#14 x 5"	500	DMIP41450D
#14 x 7"	500	DMIP41470D

3" and 4" lengths are fully threaded otherwise 4" of thread under the head.

Installation

#2 square drive suggested.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device. Suggested 1800 rpm.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Suggested 1" minimum penetration into substrate.

Limitations: Not recommend for installation by impact drivers. Contact DMI for MSDS information
All sizes not available to ship from all Service Centers.

To find a distributor call 855-800-8878 or visit www.directmetalsinc.com