

PanclipSD SS 410 MTM Fastener



Features:

- PanclipSD SS Low profile pancake for panel clip installation into metal substrates up to 8ga.
- Additional uses include fastening of articles to steel or aluminum tube when a low profile head is required.
- 410 Stainless Steel construction for strength and compatibility with many types of steel substrates. Corrosion resistant coating tested to ASTM G85-11, Annex5 and TAS114, appendix E for extended surface corrosion resistance.
- Miami-Dade Certification Listing # L-15-0518.08.
- DMG85 silver coating to help combat dissimilar metal reactions.

#10-16 Specifications

Tensile Strength: 1900 lbs ult

Torsional: 76 in-lbs

Shear: (14 ga) 1448 lbs ult

Pull out :

12 ga 1400 lbs ult

14 ga 860 lbs ult

16 ga 579 lbs ult

18 ga 423 lbs ult

22 ga 216 lbs ult

Above values are average ultimate values. Values may change with strength and condition of substrate.

Selection

Sizes / Point	Qty/Box	Part#	Dade Listing#
#10-16 x 3/4" SD3	5,000	DMIP41075D	L15-0518.08
#10-16 x 1" SD3	5,000	DMIP41010D	L15-0518.08
#12-14 x 1" SD3	2,500	DMIP41210D	
#12-14 x 2" SD3	2,000	DMIP41220D	

Installation

#2 square driver is used for installation.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Suggested for metal substrates up to 8 ga.

Contact DMI at 855-800-8878 with questions.

Limitations: Not recommended for installation by impact drivers.