
ZXL STEELZIP Longlife Self Drilling Fasteners

Designed for the attachment of metal roofing and sidewall panels to steel purlin substrates

- Lifetime 40 Year Warranty Long Life Fastener.
- Fastener designed to attach long-life metal roof panels such as GALVALUME that are used in pre-engineered metal building applications.
- 5/16" Cupped HWH ZAMAC Zinc-Aluminum Alloy provides lifetime protection against red rust on the head.
- Washer face design helps to capture rubber EPDM washer even when driven at an angle. #12 & 1/4" diameter drill point easily penetrates steel thickness up to .210" with no "point walking."
- 1/4" Diameter Stitch securely fastens 2 layers of 26 GA with no strip-out.







ENGINEERED DRILL POINT FOR HIGH TENSILE STEEL--NO POINT WALKING

Specifications

Torsional: 92 in-lbs

Tensile: 2,240 lbs. min.

Shear: 1,962 lbs min.

Pull out 12ga 1678 lbs ult Pull out 14ga 958 lbs ult Pull out 16ga 927 lbs ult

Painted Fasteners qualify for Buy American Plan.

Standard colors are powder coat head painted.

Approximated values are average ultimate values. Values may change with strength and condition of substrate.

Installation

DMI Spring Clip Drivers Suggested

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Suggested drill speed is most substrates is 1800 rpm.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Selection

Available Sizes	Drill Point/HD	Qty/Box	Part#
#12-14 x 1"	SD3 5/16"H	2,000	DMI3ZXL312100
#12-14 x 1-1/4"	SD3 5/16"H	2,000	DMI3ZXL312125
#12-14 x 1-1/2"	SD3 5/16"H	1,500	DMI3ZXL312150
#12-14 x 2"	SD3 5/16"H	1,500	DMI3ZXL312200
#12-14 x 3"	SD3 3/8"H	1,000	DMI3ZXL312300
1/4-14 x 1-1/4"	SD3 3/8"H	1,500	DMI3ZXL314125
1/4-14 x 7/8"	SD1 5/16"H	2,000	DMI3ZXL114078

Limitations: Not recommend for installation by impact drivers.

Contact DMI for MSDS information

To find a distributor of DMI products please visit www.directmetalsinc.com or call 855-800-8878