

# XLP\*CON



The new XLP\*CON is designed for the installation of windows into wood buck or masonry/concrete substrates. Design features improved installed appearance and holding power of typical competing fasteners. The XLP\*CON is also used to secure roofing bearing plates through insulation and into concrete substrates.

## Features:

- Panclip XLP Extra Low profile pancake/wafer head designed for the ultimate low profile fastening without countersinking the fastener.
- XLP head has a smaller shoulder than competing trim head fasteners allowing for a flush installation with additional clamping power.
- DMG95 anti-corrosion coating covers the complete fastener. This fastener exceeds Florida Building Code HVHZ and Miami-Dade County corrosion resistance requirements ASTM G85 Annex A5 TAS 114, Appendix E. Miami-Dade Listing # L 19-0219.04

MIAMI-DADE COUNTY  
LISTED

## Specifications

1/4 Diameter, #2 Square Drive, Diamond Point

Thread: Hilo , Masonry / Wood

Double Shear: 5490 lbs average ultimate

Corrosion Resistance:

ASTM B117: 1500 HRS

ASTM G85 Annex A5 TAS 114, Appendix E.

COO: Taiwan

## Installation

#2 square drive installation tool required.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Suggested 1" minimum penetration into substrate.

Masonry Pre-Drill with 3/16" diameter drill bit.

Pre-drill hole minimum of 1/2" deeper than fastener penetration. Clean hole before install.

## Selection

<u>Sizes</u>	<u>Part#</u>	<u>Color</u>
#14 x 2-3/4"	DMIPCX234WW	White
#14 x 2-3/4"	DMIPCX234WB	Bronze
#14 x 3-1/4"	DMIPCX325WW	White
#14 x 3-1/4"	DMIPCX325WB	Bronze

Packaging is 100 pieces per box with 16 boxes per carton. Each box includes one predrill Drill bit and one installation drill bit.

