HWH Impax / STEELZIP HG Self Drilling Fasteners



Features:

- Precision forged self drilling points for metal to metal fastening
- Galvanized plating plus VistaCoat or DMG85 long life full fastener coating for corrosion protection to meet FBC requirements.
- HWH head for stable drilling performance

Application:

- Designed for metal to metal applications such as purlin to purlin, sheet metal to purlin and plate to purlin fastening.
- Drill and Tap capabilities are matched to required thread patterns.

Specifications

1/4-20 values

Torsional: 156 in-lbs
Tensile: 4,200 lbs. min.
Shear: 2,920 lbs min.

Withdrawl: Pull out 12ga 1532 lbs ult

Pull out 1/4" Exceeds Tensile of 4200 lbs
Pull out 3/8" Exceeds Tensile of 4200 lbs
Pull out 1/2" Exceeds Tensile of 4200 lbs

Head Drive: 3/8" HWH

Drill Capacity: 0.105" - 0.5000"


Thread Maj: 0.245"
Thread Min: 0.192"

Washer (If assembled) 19/32" Galv / EPDM Bonded

COO: Consult sales person some parts are manufactured in Taiwan some parts are manufactured in the U.S.A.

Approximated values are average ultimate values. Values may change with strength and condition of substrate.

Selection



Limitations: Not recommend for installation by impact drivers. Not for use with Aluminum or Copper Metals.

Installation: 3/8" Hex magnetic driver, 0-2000 rpm electric screw gun with depth sensing nose piece or torque control device. Fastener

length should provide for a minimum of 3/16" penetration of fully developed threads into metal substrate. .

MSDS: Contact DMI for MSDS information