

# #10 WOODMAC

## WOODZIP S.C.A.M.P. 304 STAINLESS STEEL CAP HEAD

The Woodmac is designed to provide the cut and hold performance of the WoodZIP fastener with the added corrosion protection of a 1/4" drive 304 series stainless steel head.



### Features:

- 304 Stainless Capped Head that encapsulated the EPDM seal washer
- Zinc Plated Carbon Steel Shank
- TP-17 Cut point allow stab and drill speedy installation and reduces penetration shavings

## Specifications

1/4 CHWH, TP-17 Point MTW

Torsional: 60 in-lbs  
Tensile: 1,751 lbs. min.  
Shear: 1,223 lbs min.

Tension/Pull-out testing

#10 Pull out Substrate	#10 Pull out Ultimate Value
1" x 4" SYP Pine	524 lbs
1/2" Plywood	
3/4" Plywood	

Values are ultimate values. Values may change with strength and condition of substrate wood.

## Selection

Sizes	Qty/Box	Part#	Coating
#10 x 1"	2,500	DMI2CO168CAF	NA Zinc Plated
#10 x 1-1/2"	2,000	DMI2CO268CAF	NA Zinc Plated
#10 x 2"	1,500	DMI2CO388CAF	NA Zinc Plated
#10 x 2-1/2"	1,000	DMI2CO468CAF	NA Zinc Plated

All above size are packaged 250 pieces per bag

Most sizes are available painted to complement metal roofing colors.

## Installation

1/4 Hex driver required for #10

LSC drivers are suggested.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Suggested drill speed in most substrates is 1800 rpm.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Suggested 1" minimum penetration into substrate.

**Limitations:** Not recommended for pressure treated wood substrates. Not recommended for copper or aluminum roofing panels. Not recommended for installation by impact drivers. Contact DMI for MSDS information

**To find a distributor call 855-800-8878 or visit [www.directmetalsinc.com](http://www.directmetalsinc.com)**