

Direct*Seal ZXL FL w/M-Bit



Designed as a long life metal roofing and sidewall panel fastener for installation into wood substrates. The FL ZXL was specifically designed with a bonded washer popular for the installation of 5V Crimp metal panels to wood substrate.

Features:

- The Micro-Bit drill point reduces metal pig-tails/shavings that can be embedded into the washer
- 5/16" cupped style ZAMAC head that encapsulates the bonded washer (specific to the FL Screw) .
- Lifetime warranty and protection against red rest on the head



Selection

<u>Mill Finish Sizes</u>	<u>Qty/Box</u>	<u>Part#</u>	<u>Weight/1000</u>
#10 x 1-1/2"	2,000	DMI3ZXLB10150	16.0 lbs

<u>1-1/2" Colors</u>	<u>Part#</u>
ASH GRAY 850	DMI3ZXLB10150850
BURNISHED SLATE 042	DMI3ZXLB10150042
CARIBBEAN BLUE 012	DMI3ZXLB10150012
CHARCOAL 051	DMI3ZXLB10150051
COCOA BROWN 110	DMI3ZXLB10150110
EVERGREEN 232	DMI3ZXLB10150232
GALLERY BLUE 843	DMI3ZXLB10150843
LIGHT STONE 248	DMI3ZXLB10150248
RED 890	DMI3ZXLB10150890
TAN 020	DMI3ZXLB10150020
WHITE 001	DMI3ZXLB10150001

Packaging:

250 pcs/bag, 8 bags per box, 48 box / pallet, 26 pallets/ truck.

Specifications

Typical Specifications #10 SD1
5/16" AFH Hex Drive, MTW

Pull out
SYP Wood 1" penetration
S. Yellow Pine 713 lbs ult
Pull out 1/2" PLY 368 lbs ult
Pull out 7/16" OSB(NOM1/2) 210 lbs

Installation

5/16" hex driver required, DMI LSC 5/16" suggested.
0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Suggested drill speed into most substrates is 1800 rpm.
Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Place point on panel and apply pressure before triggering installation tool. Trigger and apply pressure and let the drill point do the work. Always clean surfaces of debris/shavings after installation.

Limitations: Not recommended for aluminum or copper roofing panels.
Not recommended for installation by impact drivers. Contact DMI for MSDS information



To find a distributor call 855-800-8878 or visit www.directmetalsinc.com