

# S.C.A.M.P. 304SSC METAL BUILDING REPAIR AND REPLACEMENT FASTENERS



The SteelZip SCAMP (Stainless Cap And Metal Point) self drilling fastener offers the installed protection of stainless steel without the cost and installation challenges of a full 304 stainless steel fastener. The SCAMP provides torsional and tensile strengths of a carbon steel fastener with the installed exterior corrosion resistance of stainless steel.

## Features:

- 304 Series Stainless Steel Capped Head
- Non-walking precision drill point to drill and tap steel substrates.
- Thick EPDM seal washer, DMG85 corrosion resistant shank coating.
- Lifetime warranty against red rust corrosion on head of fastener.
- Miami-Dade County Product Listing # L 20-1105.01 (#14 SCAMP)



## Selection

Listing # L 20-1105.01.

MIAMI-DADE COUNTY LISTED

Size	Application	Qty/Box	Part#
1/4-14 x 1-1/4"	METAL SD3	1,500	DMI4SSCSD314125M
1/4-14 x 1-3/4"	METAL SD5	1,000	DMI4SSCSD514134M
5/16 x 1-1/4"	METAL SD3	1,000	DMI4SSCSD3516125M
Size	Application	Qty/Box	Part#
3/8" x 1"	METAL	1,000	DMI4SSC380100M

## Self Drilling Screw Specifications

#14 (1/4-14) Fasteners are suitable for direct replacement of #8, #10 and #12 self drilling fasteners.

5/16" Fasteners are suitable for direct replacement of #12, #14, #17 and other fasteners with an outside diameter smaller than 0.31"

Testing for Florida Building Code High Velocity Hurricane Zone : TAS 114, Appendix E , ASTM G85 Annex A5. Complies for 1000 hr exposed applications. Complies with 2017 Florida Building Code R904.5.2 requirements.

Tested for Miami-Dade Fastener Listing: TAS 114, Appendix E, ASTM G85 Annex A5. Complies with 1000 hr exposed applications fastener listing number issued, Listing # L 20-1105.01. ANSI/ASME B 18.6.1 COO: Taiwan

Shear Testing : Double Shear #14(1/4-14)2,385 lbs avg.

Drill Point Capabilities:

#3 point drills .036" - .210" material  
#5 point drills .125" - .500" material



## 3/8" Self Tapping Screw Specifications

3/8" SCAMP Tapper fasteners are designed to be used as a replacement fastener into steel and metal substrates.

3/8" Fasteners are suitable for replacement of bumble bee fasteners 0.343" and 0.359" tapping screws. These tapping screws are commonly seen in a yellow zinc finish. A pre-drill of steel purlin substrates will be required. Also popular for replacing #17 stitch / panel lap fastener as a direct replacement without predrilling.

Corrosion resistant DMG85 coatings co complies with 2017 Florida Building Code R904.5.2 requirements. ANSI/ASME B 18.6.1 COO: Taiwan



To find a distributor call 855-800-8878 or visit [www.directmetalsinc.com](http://www.directmetalsinc.com)