

# 125 Multi-Seal®

ROOFING • GUTTERS • CONCRETE • CONSTRUCTION



- Plastic cartridge
- One year shelf life
- Applies the same in all seasons
- Bonds to wet, damp surfaces
- Long lasting, flexible adhesive
- Many colors available
- Paintable in under an hour\*
- Qualifies for LEED Credits
- VOC compliant
- Bonds to Kynar® 500

Kynar® 500 is a trademark of Arkema Inc.  
\*Translucent is not paintable

## THE IDEAL SEALANT/ADHESIVE FOR:

- Roofing
- Flashing
- Vents
- Gutters
- Tiles
- Wood
- Concrete
- Curbs
- Downspouts
- Pinhole repairs
- Masonry joints
- Exterior mastic
- Aluminum angle joints
- Asphalt shingles
- Window & door perimeter joints
- Facade & metal clapping joints
- Concrete construction joints
- **MANY MORE...**

### Colors:

- Cartridge**
- White - 12501
  - Black - 12502
  - Grey - 12503
  - Limestone - 12507
  - Alum/Grey - 12513
  - Hunter Green - 12514
  - Medium Bronze - 12515
  - Off White - 12516
  - Redwood Tan - 12517
  - Stone - 12518
  - Tan - 12519
  - Special Bronze - 12520
  - Brown - 12521
  - Translucent - 12522

### TYPICAL PROPERTIES

	Colors	Translucent
<b>Uncured</b>		
Flow Sag or Slump	NIL	NIL
Tack Free Time	20 min.	20 min.
Extrusion Rate	400 g/min.	300 g/min.
<b>Cured – Physical</b>		
<b>7 Days at 77°F (25°C) and 50% RH (1/8" thickness)</b>		
Durometer Shore A Hardness	35 points	17 points
Specific Gravity	1.53	1.01
Tensile Strength	180 psi	180
Elongation	350%	480%
Modulus	130 psi	50 psi
Shrinkage	NIL	NIL
Service Temperature	-40°F to 200°F	
Application Temperature	-35°F to 140°F	

Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal.

### LIMITATIONS

- Do not use for structural glazing
- It is the sole responsibility of the user to test the adhesion to the substrate for suitability

### CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF THE REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

# BOSS<sup>®</sup> PRO

12501 White

12523 Artic White

12507 Limestone

12517 Redwood Tan

12514 Hunter Green

12521 Brown

12515 Medium Bronze

12519 Tan

12518 Stone

12513 Aluminum Grey

12503 Grey

12520 Special Bronze

12502 Black

12522 Translucent

# 125

## MULTI-SEAL<sup>®</sup>

ROOFING · GUTTERS  
CONSTRUCTION  
METAL

Door & Window  
Perimeter  
Joints

Asphalt  
Shingles

Aluminum  
Angle Joints

Curbs

Many More!

**Bonds to Kynar 500<sup>®</sup>  
VOC Compliant**