

## TERMINATION BAR

The DEK-ZIP TERM BAR for edge or vertical parapet wall terminations.

- 6063-T6 ALUMINUM CONSTRUCTION FOR CORROSION RESISTANCE
- INTEGRAL REINFORCEMENT RIBS
- 6" ON CENTER FASTENER HOLES
- 10' LONG PIECES, 50 PIECES/TUBE
- USE WITH #12, #14 OR #15 FASTENERS
- SEALANT LEDGE "LIP" BAR AVAILABLE
- FLAT BAR AVAILABLE







### Term Bar Selection Guide

Size	Part#	Quantity/Tube
Flat	DMI9RTBF10A	500 Inft / 50 pcs
Lip / Ledge	DMI9RTBF10A	500 Inft / 50 pcs

## TERMINATION BAR ANCHORS

DMI solutions for term bar anchoring.

- NAILIN HAMMER DRIVE PIN MASONRY ANCHORS 7/8" TO 3" IN LENGTH WITH A ZINC PLATED OR STAINLESS STEEL PIN 
- PAN\*CON STAINLESS STEEL REMOVABLE SCREW MIAMI-DADE LISTED MASONRY ANCHOR 
- DIRECT\*SEAL MP MULTIPURPOSE ECONOMY FASTENER WITH BONDED SEALING WASHER INSTALLS INTO MASONRY, WOOD OR LIGHT GAUGE STEEL 
- CON\*ZIP SCAMP THE PREMIUM PERFORMANCE REMOVABLE MASONRY ANCHOR WITH BONDED SEALING WASHER AND STAINLESS STEEL PROTECTIVE 5/16" HEX HEAD DMICSSC14150M, 250/BAG, 1000/BOX. 

## SPECIALTY APPLICATION COMMERCIAL FASTENERS

### PURLIN FASTENERS - PANCLIP SD

- #3 OR #4 PRECISION FORMED DRILL POINTS
- SQUARE DRIVE FOR DRIVING STABILITY
- COATED WITH DMG85 SILVER 1000 HR COATING FOR CORROSION RESISTANCE
- EXCEEDS FL BUILDING CODE 1506.5 CORROSION RESISTANCE STANDARD REQUIREMENT
- 1/4-14 AND 1/4-20 FASTENERS WITH LENGTHS FROM 1-1/4" UP TO 10"



### CONCRETE FASTENERS - PAN\*CON


- #14 x 1-1/2", 2-3/4", 4" & 6" LENGTHS
- #2 SQUARE DRIVE FOR DRIVING STABILITY
- NOTCHED HI-LO THREAD FOR REDUCED DRIVING TORQUE
- DIAMOND LOCATOR POINT
- 410 STAINLESS STEEL CONSTRUCTION
- COATED WITH DMG85 SILVER CORROSION RESISTANT COATING
- MIAMI-DADE FASTENER LISTING CERTIFICATION FOR CORROSION RESISTANCE L#19-0216.03



### #14 STAINLESS STEEL FASTENERS PANCLIP SD-SS-L MULTI-PURPOSE

THE SD-SS-L fastener is designed for insulation or membrane attachment to wood, concrete, or steel deck in highly corrosive areas.

- FULL 410 STAINLESS STEEL CONSTRUCTION
- DMG85 SILVER FULL 1000 HR CORROSION RESISTANT COATING
- FBC 1506.6 CODE COMPLIANT
- STABILITY FROM #2 SQUARE DRIVE
- SD1 POINT CUTS THROUGH BUR AND COVER BAORDS AND WILL SECURE INTO WOOD OR METAL UP TO 18 GA
- IDEAL FOR CONCRETE WITH PRE-DRILL
- #14-13 x 1-1/2", 3", 5", 7" & 10" LENGTHS



## DEK-ZIP

LOW SLOPE COMMERCIAL ROOFING FASTENERS AND COMPONENTS



YOUR DMI DISTRIBUTOR IS:

## HD DEK-ZIP SCREWS

### #14 HD LOW SLOPE FASTENERS

The #14-10 DEK-ZIP fastener is designed for insulation or membrane attachment to wood, concrete and light gauge metal decking.

- 11 LENGTHS AVAILABLE FROM 2" - 12"
- PRECISION SD#1 DRILL POINT
- BLACK EPOXY 1000 HR COATING, CORROSION RESISTANT TO FM 4470 STANDARD ASTM D6294, DIN50018 SFW2.0S.
- COMPATIBLE WITH STANDARD SEAM AND STRESS PLATES
- PACKAGED IN JOBSITE FRIENDLY RE-SEALABLE PLASTIC PAILS
- PHILLIPS #3 DRIVE



### Fastener Selection Guide

Size	Part#	Quantity/Pail
#14 x 2"	DMICRS114200	1,000
#14 x 3"	DMICRS114300	1,000
#14 x 4"	DMICRS114400	1,000
#14 x 5"	DMICRS114500	1,000
#14 x 6"	DMICRS114600	1,000
#14 x 7"	DMICRS114700	500
#14 x 8"	DMICRS114800	500
#14 x 9"	DMICRS114900	500
#14 x 10"	DMICRS1141000	500
#14 x 11"	DMICRS1141100	500
#14 x 12"	DMICRS1141200	500

## XHD DEK-ZIP SCREWS

### #15 XHD LOW SLOPE FASTENERS

The #15-13 DEK-ZIP fastener is designed for insulation or membrane attachment to wood, concrete and light gauge metal decking.

- 18 LENGTHS AVAILABLE FROM 1-1/4" - 24"
- PRECISION SD#1 DRILL POINT
- BLACK EPOXY 1000 HR COATING, CORROSION RESISTANT TO FM 4470 STANDARD ASTM D6294, DIN50018 SFW2.0S.
- COMPATIBLE WITH STANDARD SEAM AND STRESS PLATES
- PACKAGED IN JOBSITE FRIENDLY RE-SEALABLE PLASTIC PAILS
- PHILLIPS #3 DRIVE



### Fastener Selection Guide

Size	Part#	Quantity/Pail
#15 x 1-1/4"	DMICRS115114	1,000
#15 x 2"	DMICRS115200	1,000
#15 x 3"	DMICRS115300	1,000
#15 x 4"	DMICRS115400	1,000
#15 x 5"	DMICRS115500	500
#15 x 6"	DMICRS115600	500
#15 x 7"	DMICRS115700	500
#15 x 8"	DMICRS115800	500
#15 x 9"	DMICRS115900	500
#15 x 10"	DMICRS1151000	500
#15 x 11"	DMICRS1151100	500
#15 x 12"	DMICRS1151200	250
#15 x 14"	DMICRS1151400	250
#15 x 16"	DMICRS1151600	250
#15 x 18"	DMICRS1151800	250
#15 x 20"	DMICRS1152000	250
#15 x 22"	DMICRS1152200	250
#15 x 24"	DMICRS1152400	250

## DEK-ZIP PLATES

### STRESS PLATES

The DEK-ZIP galvalume stress plate is designed to distribute clamping load and prevent fastener pull through. Ideal for insulation and cover board attachment to wood, steel or concrete roofing decks.

- AZ50 GALVALUME CONSTRUCTION FOR CORROSION RESISTANCE
- SAE J1392 SPEC 0.019" THICK GALVALUME
- 3" DIAMETER
- MULTIPLE RIB DESIGN FOR STRENGTH
- RECESSED FASTENER HOLE FOR LOW INSTALLED PROFILE
- FLAT BOTTOM
- USE WITH #12, #14 OR #15 FASTENERS
- PACKAGED IN JOBSITE FRIENDLY RE-SEALABLE PLASTIC PAILS



### Insulation Plate Selection Guide

Size	Part#	Quantity/Pail
3"	DMIP3GVP	1,000

### BARBED STRESS PLATES

The DEK-ZIP barbed galvalume seam plate is designed for membrane attachment to wood, steel or coverboard.

- AZ50 GALVALUME CONSTRUCTION FOR CORROSION RESISTANCE
- 22GA GALVALUME
- 2-3/8" DIAMETER
- MULTIPLE RIB DESIGN FOR STRENGTH
- RECESSED FASTENER HOLE FOR LOW PROFILE
- USE WITH #12, #14 OR #15 FASTENERS
- PACKAGED IN JOBSITE FRIENDLY RE-SEALABLE PLASTIC PAILS



### Membrane Plate Selection Guide

Size	Part#	Quantity/Pail
2-3/8"	DMIP2GVP	1,000