

# DEK\*ZIP #14 HD ROOFING FASTENER



The #14-10 DEK-ZIP fastener is designed for insulation or membrane attachment to wood, concrete and light gauge metal decking. Popular for use in low slope, built up and commercial roofing applications. Also used as a metal roofing panel clip fastener through multi-thickness insulation into metal deck or wood substrates.

- 11 LENGTHS AVAILABLE FROM 2" - 12"
- PRECISION SD#1 DRILL POINT
- BLACK 1000 HR COATING, CORROSION RESISTANT TO FM 4470 STANDARD
- ASTM D6294, DIN50018 SFW2.0S.
- COMPATIBLE WITH STANDARD SEAM AND STRESS PLATES
- PACKAGED IN JOBSITE FRIENDLY RE-SEALABLE PLASTIC PAILS
- PHILLIPS #3 DRIVE
- COMPATIBLE WITH DMI METAL ROOFING PANEL CLIPS



## Specifications

Head Style: Phillips PH3 Drive  
Point: Self Drill #1  
Drill Point Capacity: Drill and tap metal up to 18 ga  
Thread: Truss 10 TPI  
C1020 Carbon steel fasteners heat treated for ductility

Strength	Average Value
Tensile	3,980 lbs
Shear	2,768 lbs
Torsional	141 in lbs

Pull Out , Withdrawal	Steel Substrate Avg Value
16 ga	940 (50.0 KSI)
18 ga	453 (33.0 KSI)
22 ga	405 (80.0 KSI)
24 ga	301 (36.5 KSI)

Pull Out , Withdrawal	Wood Substrate Avg Value
2X SYP Pine	1647 lbs (1.5" Embedment)
1/2" Plywood	551 lbs

Features a corrosion resistant black epoxy coating.  
Corrosion resistant to :  
FM 4470 Standard  
ASTM D6294  
DIN50018 SFW2.0S  
FBC 1506.6 ASTM B117 1000 Hours

## Selection

<u>Size</u>	<u>Part #</u>	<u>Qty/Pail</u>
#14 x 2"	DMICRS114200	1,000
#14 x 3"	DMICRS114300	1,000
#14 x 4"	DMICRS114400	1,000
#14 x 5"	DMICRS114500	1,000
#14 x 6"	DMICRS114600	1,000
#14 x 7"	DMICRS114700	500
#14 x 8"	DMICRS114800	500
#14 x 9"	DMICRS114900	500
#14 x 10"	DMICRS1141000	500
#14 x 11"	DMICRS1141100	500
#14 x 12"	DMICRS1141200	500

Direct Metals Inc. P 855-800-8878 F 855-800-8877 [orders@directmetalsinc.com](mailto:orders@directmetalsinc.com)

Distributor and O.E.M. Manufacturer Sales Only. Contact DMI for MSDS.