

# 185 Multi-Seal<sup>®</sup>

## QUICK GRAB INDUSTRIAL • CONSTRUCTION



A one component, high performance adhesive/sealant formulated with USP™ technology. Provides excellent durability, maximum adhesive strength and is VOC compliant in 50 states. It is color stable and UV resistant (non-yellowing) and contains no isocyanates solvents halogens or acids. It is a moisture curing sealant that remains flexible, even at low temperatures with quick grab strength and excellent adhesion to various substrates such as aluminum, steel, glass, wood, brick concrete, mirrors and many plastics. It is also paintable with most latex paints.



- Fast Cure
- Quick Grab
- Formulated with USP™ Technology
- VOC Compliant
- UV resistant and color stable
- Paintable with most latex paints
- Can be applied on wet surfaces

### TYPICAL PROPERTIES

	Colors	Translucent
<b>Uncured</b>		
Flow Sag or Slump .....	NIL .....	NIL .....
Tack Free Time .....	.20 min.....	.20 min.....
Extrusion Rate .....	400 g/min. ....	300 g/min.....
<b>Cured – Physical</b>		
<b>7 Days at 77°F (25°C) and 50% RH (1/8" thickness)</b>		
Durometer Shore A Hardness .....	35 points.....	17 points.....
Specific Gravity .....	1.53.....	1.01.....
Tensile Strength.....	180 psi.....	180.....
Elongation .....	350%.....	480%.....
Modulus.....	130 psi.....	50 psi.....
Shrinkage .....	NIL.....	NIL.....
Service Temperature.....	-40°F to 200°F	
Application Temperature .....	-35°F to 140°F	

Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal.

### LIMITATIONS

- Do not use for structural glazing
- It is the sole responsibility of the user to test the adhesion to the substrate for suitability

### CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF THE REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).