

# 231 Sealant/ Adhesive



- Exceptional elongation and flexibility
- Excellent adhesion to many building surfaces, even when damp
- Remains flexible
- UV resistant
- Paintable\*
- Asphalt shingle compatible
- Easily applied, non-stringing formulation
- Tools and cleans up easily

\*Test small area for compatibility before painting

## THE IDEAL SEALANT/ADHESIVE FOR:

- Asphalt shingles
- Coated Steel  
(Kynar 500® based finishes)
- Concrete
- Vinyl
- Steel
- Other common roofing substrates

### TYPICAL PROPERTIES

Basis.....	Styrene Acrylate
Consistency.....	Paste
Curing system .....	Physical drying
Skin formation* .....	(73°F/50% R.H.) Ca. 10 min
Density** .....	Ca. 0.95 g/ml
Maximum allowed distortion .....	10 %
Service Temperature.....	-4°F to 200°F
Application Temperature .....	40°F to 90°F
Shrinkage .....	Ca. 20%

\* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal.

### LIMITATIONS

- Do not use for structural glazing
- Do not use as a window glazing sealant
- Not recommended for use on PE, PP or PTFE (Teflon®) due to poor adhesion to these substrates

### CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF THE REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).