

DMI T3 ECONO BUTYL TAPE



Product Overview: T3 is a tacky, highly elastomeric butyl tape formulated for use in the HVAC industry. DMI T3 Butyl Tape is a non-drying compound that does not stain and remains permanently flexible. In addition to providing superb adhesion to a variety of substrates, this material also prevents or reduces galvanic corrosion, noise transmission, and thermal transfer vibration. It withstands prolonged exposure to high temperatures and does not char, sag, or emit odor when heated.

Product Uses: DMI T3 Butyl Tape adheres to all common industrial grade steel, including Galvalume, Zinalume, and Kynar 500. It is designed specifically to seal against air, dust, and moisture intrusion in ductwork. Apply a complete, uninterrupted bead around the perimeter flange of adjoining duct pieces to establish a permanent, sealed gasket.



Made in the U.S.A.

Specifications

Color: Black, Odorless Rubber Based Mastic
Tensile (ASTM C907) 12-14 psi
Cone Penetrations 10.5-11.5mm@77degF
Specific Gravity 1.55 - 1.65
Solids Content (ASTM C771-74) 100 %
Application Temp -5degF to 120 degF
Elongation (ASTM D412) >800%
COO Made in the U.S.A.

Installation

For most efficient usage, ensure all involved surfaces are clear and dry, although light films of lubricant on unpainted metals should not adversely affect performance. Press onto one surface, strip paper backing, and then contact with second surface. Safely and immediately dispose of release paper.

DMI does not test applications or field conditions for this product as it may vary per application, and must be tested as an assembly.

Selection

Available Sizes Qty/Box

Single Bead

3/32" x 3/4" x 50' 16
Part# DMBTERVTB3320345045

3/32" x 1" x 35' 16
Part# DMBTERVTB33210035

3/16" x 5/8" x 25' 20
Part# DMBTERVTB31605825

Multi Bead

3/16" x 7/8" x 20' 16
Part# DMBTERVTB31607820

3/16" x 2-1/2" x 20' 8
Part# DMBTERVTB31625020

Other sizes are available and can be made to order, minimums may apply.

Safety, No special requirements are needed. Based on current data, this product is not hazardous in the meaning of the Hazardous Material Regulations. Do not eat. We recommend that you take care, in use and disposal of this product. Make sure to dispose of adhesive release paper immediately after peeling, do not leave on roof surface.

To find a distributor call 855-800-8878 or visit www.directmetalsinc.com